



## **HIP2101IB Information**



For Reference Only

Part Number HIP2101IB
Manufacturer Intersil

Category Integrated Circuits (ICs)

**PMIC - Gate Drivers** 

DescriptionIC DRIVER HALF-BRIDGE 8-SOICPackage8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HIP2101IB Specifications**

Manufacturer Part Number  Manufacturer  Category  Integrated Circuits (ICs)  PMIC - Gate Drivers  Package  8-SOIC (0.154", 3.90mm Width)  Series  - Driven Configuration  Half-Bridge Channel Type Independent Number of Drivers  2 Gate Type N-Channel MOSFET  Voltage - Supply Voltage - VIL, VIH 0.8V, 2.2V  Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Jons, 10ns  Operating Temperature Package / Case 8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  Report errors?		
Category  Integrated Circuits (ICs)  PMIC - Gate Drivers  Package  8-SOIC (0.154", 3.90mm Width)  Series  - Driven Configuration  Half-Bridge  Channel Type Independent  Number of Drivers  2  Gate Type N-Channel MOSFET  Voltage - Supply Voltage - VIL, VIH 0.8V, 2.2V  Current - Peak Output (Source, Sink) 1nput Type Non-Inverting High Side Voltage - Max (Bootstrap) 114V  Rise / Fall Time (Typ) 10ns, 10ns  Operating Temperature  Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Manufacturer Part Number	HIP2101IB
Package 8-SOIC (0.154", 3.90mm Width)  Series - Driven Configuration Half-Bridge Channel Type Independent  Number of Drivers 2 Gate Type N-Channel MOSFET  Voltage - Supply 9 V ~ 14 V  Logic Voltage - VIL, VIH 0.8V, 2.2V  Current - Peak Output (Source, Sink) 2A, 2A  Input Type Non-Inverting  High Side Voltage - Max (Bootstrap) 114V  Rise / Fall Time (Typ) 10ns, 10ns  Operating Temperature -55°C ~ 150°C (TJ)  Mounting Type Surface Mount  Mounting Type Surface Mount  Supplier Device Package 8-SOIC (0.154", 3.90mm Width)	Manufacturer	Intersil
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationHalf-BridgeChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply9 V ~ 14 VLogic Voltage - VIL, VIH0.8V, 2.2VCurrent - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)114VRise / Fall Time (Typ)10ns, 10nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series - Driven Configuration Half-Bridge Channel Type Independent Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 9 V ~ 14 V Logic Voltage - VIL, VIH 0.8V, 2.2V Current - Peak Output (Source, Sink) 2A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 114V Rise / Fall Time (Typ) 10ns, 10ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package		PMIC - Gate Drivers
Driven Configuration Channel Type Independent Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 9 V ~ 14 V Logic Voltage - VIL, VIH 0.8V, 2.2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 10ns, 10ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 9 V ~ 14 V Logic Voltage - VIL, VIH 0.8V, 2.2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 10ns, 10ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers  Gate Type  N-Channel MOSFET  Voltage - Supply  9 V ~ 14 V  Logic Voltage - VIL, VIH  0.8V, 2.2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Driven Configuration	Half-Bridge
Gate Type  N-Channel MOSFET  Voltage - Supply  9 V ~ 14 V  Logic Voltage - VIL, VIH  0.8V, 2.2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  10ns, 10ns  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Channel Type	Independent
Voltage - Supply  Logic Voltage - VIL, VIH  0.8V, 2.2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  Operating Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Voltage - Supply	9 V ~ 14 V
Input Type  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 2.2V
High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Current - Peak Output (Source, Sink)	2A, 2A
Rise / Fall Time (Typ)  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	Input Type	Non-Inverting
Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	High Side Voltage - Max (Bootstrap)	114V
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	10ns, 10ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-55°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

### **HIP2101IB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HIP2101IB Payment Methods**





















## **HIP2101IB Shipping Methods**













If you have any question about HIP2101IB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com