

HJ2-L-AC100V Information



For Reference Only

Part Number HJ2-L-AC100V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 7A 100V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HJ2-L-AC100V Specifications

Manufacturer Part NumberHJ2-L-AC100VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPower Relays, Over 2 AmpsPackage-SeriesHJRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.6mACoil Voltage100VACContact FormDPDT (2 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		
CategoryRelaysPackage-SeriesHJRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.6mACoil Voltage100VACContact FormDPDT (2 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	HJ2-L-AC100V
Package - Series HJ Relay Type General Purpose Coil Type Non Latching Coil Current 11.6mA Coil Voltage 100VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Purpose	Manufacturer	Panasonic Electric Works
Package - Series HJ Relay Type General Purpose Coil Type Non Latching Coil Current 11.6mA Coil Voltage 100VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesHJRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.6mACoil Voltage100VACContact FormDPDT (2 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11.6mA Coil Voltage 100VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current11.6mACoil Voltage100VACContact FormDPDT (2 Form C)Contact Rating (Current)7ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	НЈ
Coil Current 11.6mA Coil Voltage 100VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 100VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 7A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	11.6mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	100VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Contact Rating (Current)	7A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	80 VAC
Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	30 VAC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

HJ2-L-AC100V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HJ2-L-AC100V Payment Methods



















HJ2-L-AC100V Shipping Methods













If you have any question about HJ2-L-AC100V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com