



HJ2-T-DC110V Information

Heisener.com

Part Number HJ2-T-DC110V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 110V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HJ2-T-DC110V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series HJ Relay Type General Purpose Coil Type Non Latching Coil Current 9.1mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 1250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Test Button		
CategoryRelays Power Relays, Over 2 AmpsPackage-SeriesHJRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.1mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)11 VDCOperate Time20msRelease Time20ms	Manufacturer Part Number	HJ2-T-DC110V
Package - Series HJ Relay Type General Purpose Coil Type Non Latching Coil Current 9.1mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Manufacturer	Panasonic Electric Works
Package - Series HJ Relay Type General Purpose Coil Type Non Latching Coil Current 9.1 mA Coil Voltage 110 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250 VAC, 125 VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Category	Relays
Series HJ Relay Type General Purpose Coil Type Non Latching Coil Current 9.1mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 9.1mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Package	-
Coil TypeNon LatchingCoil Current9.1 mACoil Voltage110 V D CContact FormDPDT (2 Form C)Contact Rating (Current)10 ASwitching Voltage250 V A C, 125 V D C - MaxTurn On Voltage (Max)88 V D CTurn Off Voltage (Min)11 V D COperate Time20 msRelease Time20 ms	Series	НЈ
Coil Current 9.1mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Relay Type	General Purpose
Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Coil Current	9.1mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Coil Voltage	110VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 11 VDC Operate Time 20ms Release Time 20ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms	Turn On Voltage (Max)	88 VDC
Release Time 20ms	Turn Off Voltage (Min)	11 VDC
	Operate Time	20ms
Features Test Button	Release Time	20ms
1 Catures 1 CSt Dutton	Features	Test Button
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

HJ2-T-DC110V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HJ2-T-DC110V Payment Methods





















HJ2-T-DC110V Shipping Methods













If you have any question about HJ2-T-DC110V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com