



HL05006Z2R000JJ Information



For Reference Only

Part Number HL05006Z2R000JJ

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 2 OHM 5% 50W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HL05006Z2R000JJ Specifications

Manufacturer Part Number HL05006Z2R000JJ Manufacturer Vishay Dale Category Resistors Package Radial, Tubular Series HL Resistance 2 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 350°C Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - Report errors?		
CategoryResistorsPackageRadial, TubularSeriesHLResistance2 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 350°CFeaturesMoisture ResistantCoating, Housing TypeSilicone CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.29mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	HL05006Z2R000JJ
Chassis Mount Resistors Package Radial, Tubular Facistance Resistance Power (Watts) Composition Wirewound Temperature Coefficient Soft Coating, Housing Type Mounting Feature Brackets (not included) Size / Dimension Lead Style Package / Case Radial, Tubular Chassis Mount Resistors Radial, Tubular Failure Rate Radial, Tubular Chassis Mount Resistors Radial, Tubular Failure Radial, Tubular Failure Rate Chassis Mount Resistors Adial, Tubular Failure Rate Radial, Tubular Failure Rate Chassis Mount Resistors Adial, Tubular Failure Rate Chassis Mount Resistors Adial, Tubular Failure Rate Chassis Mount Resistors Adial, Tubular Failure Rate Failure Rate Chassis Mount Resistors Adial, Tubular Failure Rate Chassis Mount Resistors Failure Rate Adial, Tubular Failure Rate Chassis Mount Resistors Failure Rate Adial, Tubular Failure Rate Chassis Mount Resistors Failure Rate Adial, Tubular Failure Rate Adial, Tubular Failure Rate Failure Rate Adial, Tubular Failure Rate Adial, Tubular Failure Rate Adial, Tubular Failure Rate	Manufacturer	Vishay Dale
PackageRadial, TubularSeriesHLResistance2 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 350°CFeaturesMoisture ResistantCoating, Housing TypeSilicone CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.29mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesHLResistance2 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 350°CFeaturesMoisture ResistantCoating, Housing TypeSilicone CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.29mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance2 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 350°CFeaturesMoisture ResistantCoating, Housing TypeSilicone CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.29mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 350°C Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	HL
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 350°C Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	2 Ohms
Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 350°C Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Tolerance	±5%
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 350°C Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	50W
Operating Temperature -55°C ~ 350°C Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - -55°C ~ 350°C Moisture Resistant Silicone Coated Silicone Coated Brackets (not included) 0.563" Dia x 4.000" L (14.29mm x 101.60mm) - Radial, Tubular	Composition	Wirewound
Features Moisture Resistant Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Silicone Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	Moisture Resistant
Size / Dimension 0.563" Dia x 4.000" L (14.29mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.563" Dia x 4.000" L (14.29mm x 101.60mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

HL05006Z2R000JJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HL05006Z2R000JJ Payment Methods



















HL05006Z2R000JJ Shipping Methods













If you have any question about HL05006Z2R000JJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com