



#### **HL1-HTM-AC115V Information**



For Reference Only

Part Number HL1-HTM-AC115V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 15A 115V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HL1-HTM-AC115V Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Power Relays, Over 2 Amps  Package		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         HL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         10.4mA           Coil Voltage         115VAC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         15A           Switching Voltage         125VAC - Nom           Turn On Voltage (Max)         92 VAC           Turn Off Voltage (Min)         34.5 VAC           Operate Time         10ms           Release Time         10ms           Features         -           Mounting Type         Chassis Mount           Termination Style         Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	HL1-HTM-AC115V
Package - Series HL Relay Type General Purpose Coil Type Non Latching Coil Current 10.4mA Coil Voltage 115VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 10ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Manufacturer	Panasonic Electric Works
Package-SeriesHLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.4mACoil Voltage115VACContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage125VAC - NomTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time10msRelease Time10msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Category	Relays
SeriesHLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.4mACoil Voltage115VACContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage125VAC - NomTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time10msRelease Time10msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 10.4mA Coil Voltage 115VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 10ms Features Mounting Type Chassis Mount Termination Style General Purpose Seneral Purpose Sen	Package	-
Coil TypeNon LatchingCoil Current10.4mACoil Voltage115VACContact FormSPDT (1 Form C)Contact Rating (Current)15ASwitching Voltage125VAC - NomTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time10msRelease Time10msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Series	HL
Coil Current Coil Voltage 115VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 7urn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 10ms Features - Mounting Type Chassis Mount Termination Style 110	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 15A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 10ms Release Time 10ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  125 VAC - Nom  Turn On Voltage (Max)  92 VAC  Turn Off Voltage (Min)  34.5 VAC  Operate Time  10ms  Release Time  10ms  Features  -  Mounting Type  Chassis Mount  Termination Style	Coil Current	10.4mA
Contact Rating (Current)  Switching Voltage  125VAC - Nom  Turn On Voltage (Max)  92 VAC  Turn Off Voltage (Min)  34.5 VAC  Operate Time  10ms  Release Time  10ms  Features  -  Mounting Type  Chassis Mount  Termination Style  15A  125VAC - Nom  92 VAC  10ms  4.5 VAC  10ms  Chassis Mount  Quick Connect - 0.187" (4.7mm)	Coil Voltage	115VAC
Switching Voltage 125VAC - Nom  Turn On Voltage (Max) 92 VAC  Turn Off Voltage (Min) 34.5 VAC  Operate Time 10ms  Release Time 10ms  Features -  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.187" (4.7mm)	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  92 VAC  Turn Off Voltage (Min)  34.5 VAC  Operate Time  10ms  Release Time  10ms  Features  - Mounting Type  Chassis Mount  Termination Style  Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	15A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  - Mounting Type  Chassis Mount  Termination Style  34.5 VAC  10ms  Chassis Mount  Quick Connect - 0.187" (4.7mm)	Switching Voltage	125VAC - Nom
Operate Time 10ms Release Time 10ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	92 VAC
Release Time 10ms  Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	34.5 VAC
Features -  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.187" (4.7mm)	Operate Time	10ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Release Time	10ms
Termination Style Quick Connect - 0.187" (4.7mm)	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.187" (4.7mm)
•		Report errors?

### **HL1-HTM-AC115V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **HL1-HTM-AC115V Payment Methods**


































If you have any question about HL1-HTM-AC115V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com