



HL2-HTM-DC12V-F Information



For Reference Only

Part Number HL2-HTM-DC12V-F
Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HL2-HTM-DC12V-F Specifications

Manufacturer Part Number HL2-HTM-DC12V-F Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series HL Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesHLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage125VAC - NomTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Manufacturer Part Number	HL2-HTM-DC12V-F
Package - Series HL Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Manufacturer	Panasonic Electric Works
Package - Series HL Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesHLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage125VAC - NomTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Non Latching Coil Type Non Latching T5mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Release Time 525ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage125VAC - NomTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Series	HL
Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 125 VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Release Time - 25ms Features	Coil Current	75mA
Contact Rating (Current) Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style 10A 125VAC - Nom 9.6 VDC 1.2 VDC Chassis Mount Quick Connect - 0.187" (4.7mm)	Coil Voltage	12VDC
Switching Voltage 125VAC - Nom Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style 1.2 VDC 25ms Chassis Mount Quick Connect - 0.187" (4.7mm)	Switching Voltage	125VAC - Nom
Operate Time 25ms Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	9.6 VDC
Release Time 25ms Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Operate Time	25ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Release Time	25ms
Termination Style Quick Connect - 0.187" (4.7mm)	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.187" (4.7mm)
		Report errors?

HL2-HTM-DC12V-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HL2-HTM-DC12V-F Payment Methods



















HL2-HTM-DC12V-F Shipping Methods













If you have any question about HL2-HTM-DC12V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com