

## HLEM4R-1RLF Information



For Reference Only

**Part Number** [HLEM4R-1RLF](#)  
**Manufacturer** Amphenol FCI  
**Category** Connectors, Interconnects  
[FFC, FPC \(Flat Flexible\) Connectors](#)  
**Description** CONN FFC TOP 4POS 1.25MM R/A  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

## Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## HLEM4R-1RLF Specifications

Manufacturer Part Number	<a href="#">HLEM4R-1RLF</a>
Manufacturer	Amphenol FCI
Category	Connectors, Interconnects <a href="#">FFC, FPC (Flat Flexible) Connectors</a>
Package	-
Series	HLEM R
Flat Flex Type	FFC, FPC
Mounting Type	Through Hole, Right Angle
Connector/Contact Type	Contacts, Top
Number of Positions	4
Pitch	0.049" (1.25mm)
Termination	Kinked Pin
FFC, FCB Thickness	0.30mm
Height Above Board	0.197" (5.00mm)
Locking Feature	-
Cable End Type	Straight
Contact Material	Phosphor Bronze
Contact Finish	Tin
Housing Material	Polybutylene Terephthalate (PBT), Glass Filled
Actuator Material	-
Features	-
Voltage Rating	200V
Operating Temperature	-55°C ~ 85°C
Material Flammability Rating	UL94 V-0

## HLEM4R-1RLF Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## HLEM4R-1RLF Payment Methods



## HLEM4R-1RLF Shipping Methods



If you have any question about HLEM4R-1RLF, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)