



HLMP-D401 Information



Part Number HLMP-D401
Manufacturer Broadcom Limited
Category Optoelectronics

LED Indication - Discrete

Description LED ORANGE DIFF 5MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HLMP-D401 Specifications

Manufacturer Broadcom Limited Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Orange Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension -			
Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Orange Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Manufacturer Part Number	HLMP-D401	
LED Indication - Discrete Package Radial Series - Color Orange Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Manufacturer	Broadcom Limited	
Package Radial Series - Color Orange Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Category	Optoelectronics	
Series - Color Orange Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm		LED Indication - Discrete	
Color Orange Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Package	Radial	
Configuration - Lens Color Orange Lens Transparency Diffused Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Series	-	
Lens ColorOrangeLens TransparencyDiffusedMillicandela Rating5.4mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 4.83mmVoltage - Forward (Vf) (Typ)1.9VCurrent - Test10mAViewing Angle60°Mounting TypeThrough HoleWavelength - Dominant602nmWavelength - Peak600nmFeatures-Package / CaseRadialSupplier Device PackageT-1 3/4Size / Dimension-Height (Max)9.19mm	Color	Orange	
Lens Transparency Millicandela Rating 5.4mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) Pist Med Wath Domed Top, 5mm (T-1 3/4), 4.83mm T-1 3/4), 4.83mm T-1 3/4, 4.83mm T-1 3/4, 4.83mm T-1 3/4 Size / Dimension - Height (Max) Piffur A. Size / Dimension - Package / Case Radial	Configuration	-	
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension Height (Max) 5.4mcd 5.4mcd 600m 6-1.3/4, 4.83mm 6.1.9V 6.00m	Lens Color	Orange	
Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 4.83mm Voltage - Forward (Vf) (Typ) 1.9V Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Lens Transparency	Diffused	
Voltage - Forward (Vf) (Typ) Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 10mA 60° Com Through Hole 602nm 602nm 602nm 602nm 602nm 600nm 600nm	Millicandela Rating	5.4mcd	
Current - Test 10mA Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 4.83mm	
Viewing Angle 60° Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Voltage - Forward (Vf) (Typ)	1.9V	
Mounting Type Through Hole Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Current - Test	10mA	
Wavelength - Dominant 602nm Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Viewing Angle	60°	
Wavelength - Peak 600nm Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Mounting Type	Through Hole	
Features - Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Wavelength - Dominant	602nm	
Package / Case Radial Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Wavelength - Peak	600nm	
Supplier Device Package T-1 3/4 Size / Dimension - Height (Max) 9.19mm	Features	-	
Size / Dimension - Height (Max) 9.19mm	Package / Case	Radial	
Height (Max) 9.19mm	Supplier Device Package	T-1 3/4	
	Size / Dimension	-	
Report errors?	Height (Max)	9.19mm	
			Report errors?

HLMP-D401 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HLMP-D401 Payment Methods


































If you have any question about HLMP-D401, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com