

HLMP-EL16-VYSDD

HLMP-EL16-VYSDD Information

Heisener.com

Part NumberHLMP-EL16-VYSDDManufacturerBroadcom LimitedCategoryOptoelectronics

LED Indication - Discrete

Description LED AMBER CLEAR 5MM ROUND T/H

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HLMP-EL16-VYSDD Specifications

Manufacturer Part Number Manufacturer Broadcom Limited Optoelectronics LED Indication - Discrete Package Radial Series - Color Amber Configuration Lens Color Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) Current - Test Viewing Angle Mounting Type Wavelength - Dominant Wavelength - Peak Broadcom Limited Broadcom Limited Radial Cotolores LeD Indication - Discrete Radial - 2 Ona		
Category Deproceded to Discrete Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant Series Cateron Radial Colorless Lens Color Colorless Lens Color Round with Domed Top, 5mm (T-1 3/4), 5.00mm Top, 5mm (T-1 3/4),	Manufacturer Part Number	HLMP-EL16-VYSDD
LED Indication - Discrete Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 8100mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle 15° Mounting Type Through Hole Wavelength - Dominant 592nm	Manufacturer	Broadcom Limited
Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 8100mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle 15° Mounting Type Through Hole Wavelength - Dominant 592nm	Category	Optoelectronics
Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 8100mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle 15° Mounting Type Through Hole Wavelength - Dominant 592nm		LED Indication - Discrete
Color Configuration Lens Color Lens Transparency Clear Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant 592nm	Package	Radial
Configuration Lens Color Colorless Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating8100mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.3VCurrent - Test20mAViewing Angle15°Mounting TypeThrough HoleWavelength - Dominant592nm	Color	Amber
Lens TransparencyClearMillicandela Rating8100mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.3VCurrent - Test20mAViewing Angle15°Mounting TypeThrough HoleWavelength - Dominant592nm	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.3V Current - Test 20mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant 8100mcd Round with Domed Top, 5mm (T-1 3/4), 5.00mm 1.5° Through Hole Sylvetimes and the state of the sta	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.3VCurrent - Test20mAViewing Angle15°Mounting TypeThrough HoleWavelength - Dominant592nm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 15° Mounting Type Through Hole Wavelength - Dominant 592nm	Millicandela Rating	8100mcd
Current - Test 20mA Viewing Angle 15° Mounting Type Through Hole Wavelength - Dominant 592nm	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.00mm
Viewing Angle15°Mounting TypeThrough HoleWavelength - Dominant592nm	Voltage - Forward (Vf) (Typ)	2.3V
Mounting Type Through Hole Wavelength - Dominant 592nm	Current - Test	20mA
Wavelength - Dominant 592nm	Viewing Angle	15°
	Mounting Type	Through Hole
Wavelength - Peak 594nm	Wavelength - Dominant	592nm
	Wavelength - Peak	594nm
Features -	Features	-
Package / Case Radial	Package / Case	Radial
Supplier Device Package T-1 3/4	Supplier Device Package	T-1 3/4
Size / Dimension -	Size / Dimension	-
Height (Max) 8.91mm	Height (Max)	8.91mm
Report erro		Report errors?

HLMP-EL16-VYSDD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HLMP-EL16-VYSDD Payment Methods



















HLMP-EL16-VYSDD Shipping Methods













If you have any question about HLMP-EL16-VYSDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com