

Heisener.com

HLMP-EL3B-VWLDD

HLMP-EL3B-VWLDD Information

Part NumberHLMP-EL3B-VWLDDManufacturerBroadcom LimitedCategoryOptoelectronics

LED Indication - Discrete

Description LED AMBER CLEAR 5MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HLMP-EL3B-VWLDD Specifications

Manufacturer Part NumberHLMP-EL3B-VWLDDManufacturerBroadcom LimitedCategoryOptoelectronicsLED Indication - DiscretePackageRadialSeries-ColorAmberConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating5700mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant590nmWavelength - Peak594nm	
Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Amber Configuration - Lens Color Coloress Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant Series - Colorless Colorless Lens Transparency Clear Round With Domed Top, 5mm (T-1 3/4), 5.00mm Through Hole Wavelength - Dominant	
LED Indication - Discrete Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 5700mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 590nm	
Package Radial Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 5700mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 590nm	
Series - Color Amber Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 5700mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 590nm	
Color Configuration Lens Color Colorless Lens Transparency Clear Millicandela Rating Cond Style/Size Mound with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) Current - Test Viewing Angle Mounting Type Through Hole Wavelength - Dominant Amber Colorless Amber Clear Round with Domed Top, 5mm (T-1 3/4), 5.00mm 2.1V Current - Test Through Hole Soon	
Configuration Lens Color Colorless Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) Current - Test Viewing Angle Mounting Type Through Hole Wavelength - Dominant Colorless Clear Round with Domed Top, 5mm (T-1 3/4), 5.00mm Top, 5mm (T-1 3/4), 5.00mm Through Hole	
Lens ColorColorlessLens TransparencyClearMillicandela Rating5700mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant590nm	
Lens TransparencyClearMillicandela Rating5700mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant590nm	
Millicandela Rating 5700mcd Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.00mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 590nm	
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.00mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant590nm	
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant 590nm	
Current - Test 20mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 590nm	
Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant590nm	
Mounting Type Through Hole Wavelength - Dominant 590nm	
Wavelength - Dominant 590nm	
Wavelength - Peak 594nm	
Features -	
Package / Case Radial	
Supplier Device Package T-1 3/4	
Size / Dimension -	
Height (Max) 12.21mm	
Report err	

HLMP-EL3B-VWLDD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HLMP-EL3B-VWLDD Payment Methods



















HLMP-EL3B-VWLDD Shipping Methods













If you have any question about HLMP-EL3B-VWLDD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com