



### **HLMP-HL30-RU000 Information**

Heisener.com

Part NumberHLMP-HL30-RU000ManufacturerBroadcom LimitedCategoryOptoelectronics

LED Indication - Discrete

**Description** LED AMBER 5MM OVAL T/H

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HLMP-HL30-RU000 Specifications**

Manufacturer Part Number         HLMP-HL30-RU000           Manufacturer         Broadcom Limited           Category         Optoelectronics           LED Indication - Discrete           Package         Radial           Series         -           Color         Amber           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         2521mcd           Lens Style/Size         Oval with Domed Top, 5.20mm x 3.80mm           Voltage - Forward (Vf) (Typ)         2.1 V           Current - Test         70mA           Viewing Angle         100°, 40°           Mounting Type         Through Hole           Wavelength - Dominant         592nm           Wavelength - Peak         595nm           Features         -           Package / Case         Radial           Supplier Device Package         5mm Oval           Rieght (Max)         7.00mm	*	
Category         Optoelectronics           LED Indication - Discrete           Package         Radial           Series         -           Color         Amber           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         2521 mcd           Lens Style/Size         Oval with Domed Top, 5.20mm x 3.80mm           Voltage - Forward (Vf) (Typ)         2.1V           Current - Test         70mA           Viewing Angle         100°, 40°           Mounting Type         Through Hole           Wavelength - Dominant         592nm           Wavelength - Peak         595nm           Features         -           Package / Case         Radial           Supplier Device Package         5mm Oval           Size / Dimension         -           Height (Max)         7.00mm	Manufacturer Part Number	HLMP-HL30-RU000
Package         Radial           Series         -           Color         Amber           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         2521 mcd           Lens Style/Size         Oval with Domed Top, 5.20mm x 3.80mm           Voltage - Forward (Vf) (Typ)         2.1 V           Current - Test         70mA           Viewing Angle         100°, 40°           Mounting Type         Through Hole           Wavelength - Dominant         592nm           Wavelength - Peak         595nm           Features         -           Package / Case         Radial           Supplier Device Package         5mm Oval           Size / Dimension         -           Height (Max)         7.00mm	Manufacturer	Broadcom Limited
Package         Radial           Series         -           Color         Amber           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         2521mcd           Lens Style/Size         Oval with Domed Top, 5.20mm x 3.80mm           Voltage - Forward (Vf) (Typ)         2.1V           Current - Test         70mA           Viewing Angle         100°, 40°           Mounting Type         Through Hole           Wavelength - Dominant         592nm           Wavelength - Peak         595nm           Features         -           Package / Case         Radial           Supplier Device Package         5mm Oval           Size / Dimension         -           Height (Max)         7.00mm	Category	Optoelectronics
Series         -           Color         Amber           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         2521mcd           Lens Style/Size         Oval with Domed Top, 5.20mm x 3.80mm           Voltage - Forward (Vf) (Typ)         2.1V           Current - Test         70mA           Viewing Angle         100°, 40°           Mounting Type         Through Hole           Wavelength - Dominant         592nm           Wavelength - Peak         595nm           Features         -           Package / Case         Radial           Supplier Device Package         5mm Oval           Size / Dimension         -           Height (Max)         7.00mm		LED Indication - Discrete
Color         Amber           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         2521mcd           Lens Style/Size         Oval with Domed Top, 5.20mm x 3.80mm           Voltage - Forward (Vf) (Typ)         2.1V           Current - Test         70mA           Viewing Angle         100°, 40°           Mounting Type         Through Hole           Wavelength - Dominant         592nm           Wavelength - Peak         595nm           Features         -           Package / Case         Radial           Supplier Device Package         5mm Oval           Size / Dimension         -           Height (Max)         7.00mm	Package	Radial
Configuration - Clens Color - Clens Transparency - Clens Transparency - Clens Transparency - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.80mm - Clens Style/Size Oval with Domed Top, 5.20mm x 3.	Series	-
Lens Color-Lens Transparency-Millicandela Rating2521mcdLens Style/SizeOval with Domed Top, 5.20mm x 3.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test70mAViewing Angle100°, 40°Mounting TypeThrough HoleWavelength - Dominant592nmWavelength - Peak595nmFeatures-Package / CaseRadialSupplier Device Package5mm OvalSize / Dimension-Height (Max)7.00mm	Color	Amber
Lens Transparency Millicandela Rating Lens Style/Size Oval with Domed Top, 5.20mm x 3.80mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 70mA Viewing Angle 100°, 40° Mounting Type Through Hole Wavelength - Dominant 592nm Wavelength - Peak 595nm Features - Package / Case Radial Supplier Device Package Size / Dimension - Height (Max) Toval with Domed Top, 5.20mm x 3.80mm Towal None	Configuration	-
Millicandela Rating Lens Style/Size Oval with Domed Top, 5.20mm x 3.80mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 70mA Viewing Angle 100°, 40° Mounting Type Through Hole Wavelength - Dominant 592nm Wavelength - Peak 595nm Features - Package / Case Radial Supplier Device Package Size / Dimension Height (Max) 7.00mm	Lens Color	-
Lens Style/SizeOval with Domed Top, 5.20mm x 3.80mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test70mAViewing Angle100°, 40°Mounting TypeThrough HoleWavelength - Dominant592nmWavelength - Peak595nmFeatures-Package / CaseRadialSupplier Device Package5mm OvalSize / Dimension-Height (Max)7.00mm	Lens Transparency	-
Voltage - Forward (Vf) (Typ)  Current - Test  70mA  Viewing Angle  100°, 40°  Mounting Type  Through Hole  Wavelength - Dominant  592nm  Wavelength - Peak  595nm  Features  - Radial  Supplier Device Package  Size / Dimension  Height (Max)  2.1V  2.1V  2.1V  RomA  RomA  RomA  100°, 40°  Through Hole  592nm  Features  - Package / Case  Radial  595nm  Oval  7.00mm	Millicandela Rating	2521mcd
Current - Test 70mA  Viewing Angle 100°, 40°  Mounting Type Through Hole  Wavelength - Dominant 592nm  Wavelength - Peak 595nm  Features - Package / Case Radial  Supplier Device Package 5mm Oval  Size / Dimension - Height (Max) 7.00mm	Lens Style/Size	Oval with Domed Top, 5.20mm x 3.80mm
Viewing Angle100°, 40°Mounting TypeThrough HoleWavelength - Dominant592nmWavelength - Peak595nmFeatures-Package / CaseRadialSupplier Device Package5mm OvalSize / Dimension-Height (Max)7.00mm	Voltage - Forward (Vf) (Typ)	2.1V
Mounting Type Through Hole  Wavelength - Dominant 592nm  Wavelength - Peak 595nm  Features - Radial  Supplier Device Package Smm Oval  Size / Dimension - Height (Max) 7.00mm	Current - Test	70mA
Wavelength - Dominant  Wavelength - Peak  592nm  592nm  595nm  Features  - Package / Case  Radial  Supplier Device Package  5mm Oval  Size / Dimension  - Height (Max)  7.00mm	Viewing Angle	100°, 40°
Wavelength - Peak 595nm  Features - Package / Case Radial Supplier Device Package 5mm Oval Size / Dimension - Height (Max) 7.00mm	Mounting Type	Through Hole
Features - Package / Case Radial Supplier Device Package 5mm Oval Size / Dimension - Height (Max) 7.00mm	Wavelength - Dominant	592nm
Package / Case Radial Supplier Device Package 5mm Oval Size / Dimension - Height (Max) 7.00mm	Wavelength - Peak	595nm
Supplier Device Package 5mm Oval Size / Dimension - Height (Max) 7.00mm	Features	-
Size / Dimension - Height (Max) 7.00mm	Package / Case	Radial
Height (Max) 7.00mm	Supplier Device Package	5mm Oval
	Size / Dimension	-
Report errors?	Height (Max)	7.00mm
Report crisis:		Report errors?

#### **HLMP-HL30-RU000 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HLMP-HL30-RU000 Payment Methods**





















## **HLMP-HL30-RU000 Shipping Methods**













If you have any question about HLMP-HL30-RU000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com