

HM2P67PD5111L9

HM2P67PD5111L9 Information

Contail lervice states teen	 HM2P67PD5111L9 Amphenol FCI Connectors, Interconnects Backplane Connectors - Hard Metric, Standard MPAC 5R ST PF HDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HM2P67PD5111L9 Specifications

ManufacturerAmphenol FCICategoryConnectors, InterconnectsBackplane Connectors - Hard Metric, StandardPackage-SeriesMillipacs?Connector TypeHeader, Male PinsConnector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedS + 2Number of Rows5 + 2Mounting TypeThrough HoleConnector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)		
CategoryConnectors, InterconnectsBackplane Connectors - Hard Metric, StandardPackage-SeriesMillipacs?Connector TypeHeader, Male PinsConnector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact Finish Thickness51.2µin (1.30µm)	Manufacturer Part Number	HM2P67PD5111L9
Backplane Connectors - Hard Metric, StandardPackage-SeriesMillipacs?Connector TypeHeader, Male PinsConnector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Manufacturer	Amphenol FCI
Package-SeriesMillipacs?Connector TypeHeader, Male PinsConnector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldSeries51.2µin (1.30µm)	Category	Connectors, Interconnects
SeriesMillipacs?Connector TypeHeader, Male PinsConnector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldStruct Finish Thickness51.2µin (1.30µm)		Backplane Connectors - Hard Metric, Standard
Connector TypeHeader, Male PinsConnector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldState Times51.2µin (1.30µm)	Package	-
Connector StyleAB 19Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldState State Sta	Series	Millipacs?
Number of Positions127 (95 + 32 Ground)Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldStruct Finish Thickness51.2µin (1.30µm)	Connector Type	Header, Male Pins
Number of Positions LoadedAllPitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldSontact Finish Thickness51.2µin (1.30µm)	Connector Style	AB 19
Pitch0.079" (2.00mm)Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Number of Positions	127 (95 + 32 Ground)
Number of Rows5 + 2Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Number of Positions Loaded	All
Mounting TypeThrough HoleTerminationPress-FitConnector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Pitch	0.079" (2.00mm)
TerminationPress-FitConnector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Number of Rows	5 + 2
Connector Usage-Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness51.2µin (1.30µm)	Termination	Press-Fit
Contact Finish Thickness 51.2µin (1.30µm)	Connector Usage	-
	Contact Finish	Gold
Report errors?	Contact Finish Thickness	51.2µin (1.30µm)
		Report errors?

HM2P67PD5111L9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

HM2P67PD5111L9 Payment Methods



HM2P67PD5111L9 Shipping Methods



If you have any question about HM2P67PD5111L9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com