

**HM71-30101LFTR Information**


For Reference Only

**Part Number** [HM71-30101LFTR](#)  
**Manufacturer** TT Electronics/BI Magnetics  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 100UH 1.3A 280 MOHM  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**HM71-30101LFTR Specifications**

Manufacturer Part Number	<a href="#">HM71-30101LFTR</a>
Manufacturer	TT Electronics/BI Magnetics
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	HM71
Type	Wirewound
Material - Core	-
Inductance	100µH
Tolerance	±20%
Current Rating	1.3A
Current - Saturation	1.2A
Shielding	Unshielded
DC Resistance (DCR)	280 mOhm Max
Q @ Freq	-
Frequency - Self Resonant	-
Ratings	-
Operating Temperature	-40°C ~ 125°C
Frequency - Test	100kHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.510" L x 0.370" W (12.95mm x 9.40mm)

Height - Seated (Max)

0.213" (5.40mm)

[Report errors?](#)

## HM71-30101LFTR Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## HM71-30101LFTR Payment Methods



## HM71-30101LFTR Shipping Methods



If you have any question about HM71-30101LFTR, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)