



HM79-40820LFTR13 Information



For Reference Only

Part Number HM79-40820LFTR13

Manufacturer TT Electronics/BI Magnetics
Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 82UH 780MA 370 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HM79-40820LFTR13 Specifications

Manufacturer TT Electronics/BI Magnetics Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series HM79 Type Wirewound Material - Core - Inductance 82µH Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Size / Dimension 0.307" L x 0.276" W (7.80mm x 7.00mm)	Manufacturer Part Number	HM79-40820LFTR13
Fixed Inductors	Manufacturer	TT Electronics/BI Magnetics
Package Nonstandard Series HM79 Type Wirewound Material - Core - Inductance 82μH Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Category	Inductors, Coils, Chokes
Series HM79 Type Wirewound Material - Core - Inductance 82µH Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -		Fixed Inductors
Type Wirewound Material - Core Inductance 82μH Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Package	Nonstandard
Material - Core - Inductance 82µH Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Series	HM79
Inductance 82μH Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Туре	Wirewound
Tolerance ±20% Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Material - Core	-
Current Rating 780mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Inductance	82µН
Current - Saturation - Shielding Unshielded DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Tolerance	±20%
Shielding DC Resistance (DCR) 370 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test IkHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current Rating	780mA
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings Operating Temperature -40°C ~ 125°C Frequency - Test IkHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - 370 mOhm Max - 370 mOhm Max - Supplier Device Package - Nonstandard	Current - Saturation	-
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Shielding	Unshielded
Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test IkHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	DC Resistance (DCR)	370 mOhm Max
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Q @ Freq	-
Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Self Resonant	-
Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Test	1kHz
Package / Case Nonstandard Supplier Device Package -	Features	-
Supplier Device Package -	Mounting Type	Surface Mount
	Package / Case	Nonstandard
Size / Dimension 0.307" L x 0.276" W (7.80mm x 7.00mm)	Supplier Device Package	-
	Size / Dimension	0.307" L x 0.276" W (7.80mm x 7.00mm)

Height - Seated (Max) 0.197" (5.00mm) Report errors?

HM79-40820LFTR13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HM79-40820LFTR13 Payment Methods



















HM79-40820LFTR13 Shipping Methods













If you have any question about HM79-40820LFTR13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com