



HMB1131K01M Information



For Reference Only

Part Number HMB1131K01M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 26.5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HMB1131K01M Specifications

Manufacturer Part Number HMB1131K01M Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Package - Series Military, MIL-R-39016/22, HMB, CII Relay Type General Purpose Coil Type Non Latching Coil Current 37.86mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/22, HMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28 VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer Part Number	HMB1131K01M
Package-SeriesMilitary, MIL-R-39016/22, HMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series Military, MIL-R-39016/22, HMB, CII Relay Type General Purpose Coil Type Non Latching Coil Current 37.86mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Category	Relays
SeriesMilitary, MIL-R-39016/22, HMB, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.86mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage28VDC - NomTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)1.5 VDCOperate Time-Release Time-FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Package	-
Coil Type Non Latching Coil Current 37.86mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Series	Military, MIL-R-39016/22, HMB, CII
Coil Current 37.86mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Current	37.86mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 1.5 VDC Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time - Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Switching Voltage	28VDC - Nom
Operate Time - Release Time - Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn On Voltage (Max)	15 VDC
Release Time - Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Turn Off Voltage (Min)	1.5 VDC
Features Sealed - Hermetically Mounting Type Chassis Mount Termination Style Solder Hook	Operate Time	-
Mounting Type Chassis Mount Termination Style Solder Hook	Release Time	-
Termination Style Solder Hook	Features	Sealed - Hermetically
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Hook
		Report errors?

HMB1131K01M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HMB1131K01M Payment Methods



















HMB1131K01M Shipping Methods













If you have any question about HMB1131K01M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com