

HMC05DRXI

HMC05DRXI Information

Heisener.com	 HMC05DRXI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 10POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HMC05DRXI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row062" (1.57mm)Number of Rows2Pich0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsContact TypeSolder Contact SectorContact Ty		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness3ujni (0.76µm)Contact TypeFull BellowsContact TypeSulle Contact TypeContact TypeSulle Contact Type </td <td>Manufacturer Part Number</td> <td>HMC05DRXI</td>	Manufacturer Part Number	HMC05DRXI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorBueFaquere-50°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFolderContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBueFange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row10Card Thickness0.062" (1.57mm)Number of Rows2Pich0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessJujin (0.76µm)Contact TypeFull BellowsColorBueFage FeatureTop Mount Opening, Threaded Insert, 4-40Forating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSipin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)TerminationSolderContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Series	-
Number of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessJujin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness Gold Contact Type Full Bellows Color Bue Flange Feature - Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessSoljui (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	5
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	10
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlueColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
Report envis.		Report errors?

HMC05DRXI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HMC05DRXI Payment Methods



HMC05DRXI Shipping Methods



If you have any question about HMC05DRXI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com