

HMC08DRYH

HMC08DRYH Information

Heisener.com	 HMC08DRYH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 16POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HMC08DRYH Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBueFlage Feature- 50°C ~ 125°C		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeNirough HoleContact MaterialSolderContact Finish Thickness0jui (0.76µm)Contact TypeFull BellowsContact TypeSuli (0.76µm)Contact TypeSuli (0.75µm)Contact TypeSuli (0.75µm)Contact TypeSuli (0.75µm)Contact TypeSuli (0.75µm)C	Manufacturer Part Number	HMC08DRYH
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeGudut Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Mounting Type-Mounting TypeSolderContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSulpane SolutionContact TypeSulpane SolutionContact TypeSulpane SolutionContact TypeSulpane SolutionContact TypeSulpane SolutionContact TypeSulpane SolutionContact TypeSulpane SolutionColorBueFlange Feature- Solor Cantact, 0.125" (3.18mm) DiaOperating Temperature- Solor Cantact, 0.25°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessSolyin 0.76µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsColorBueFlange Feature-Operating Temperature-Contage Temperature-Contage Temperature-Contact Temperature-Contact Temperature-Contact Temperature-Contact Temperature-Contact Type-Contact Type <td< td=""><td>Package</td><td>-</td></td<>	Package	-
GenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorBueFlarge FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeGuld (0.16µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-Operating Temperature-O	Card Type	Non Specified - Dual Edge
Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Solder Solder Contact Material Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	8
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	16
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HMC08DRYH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HMC08DRYH Payment Methods



HMC08DRYH Shipping Methods



If you have any question about HMC08DRYH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com