

HMM11DRKN

HMM11DRKN Information

Heisener.com	 HMM11DRKN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 22POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HMM11DRKN Specifications

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeSolderContact FinishSolderContact FinishGoldContact Finish ThicknessSolin (0.76µm)Contact TypeFull BellowsContact TypeSolin (0.76µm)Contact TypeSolin (0.76µm)Cont	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row11Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSolderContact Type<	Manufacturer Part Number	HMM11DRKN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact Type50lerContact Type50lerContact Type50lerContact Type50lerContact Type60ldContact Type60ldContact Type50lerContact Type50lerContact Type50lerContact Type50lerContact Type60ldContact Type60lellowsContact Type60lellowsContact Type60lellowsContact Type60lellowsContact Type60°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact Finish ThicknessSolderContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeFull BellowsColorBueFage Feature-Pinge Feature-Operating Temperature-Solder-Contact TinishSolderColorBlueColorBlueFeatures-Color-Solder-ColorBlueColor-Color-Solder-Color-Solder-Solder-Color-Solder-Solder-Color-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder- </td <td>Package</td> <td>-</td>	Package	-
GenderFemaleNumber of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact FinishGoldContact TypeFull BellowsColorBueFlarge Feature-Operating Temperature-Operating Temperature-Operating Temperature-	Series	-
Number of Positions/Bay/Row11Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-Solor Catt Schemer-ColorSolorColorSolorColorSolorSolorSolorColorSolorSolorSolorColorSolor <td>Card Type</td> <td>Non Specified - Dual Edge</td>	Card Type	Non Specified - Dual Edge
Number of Positions22Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-55°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	11
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	22
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)ColorFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness3/µin (0.76µm)Contact TypeFul BellowsColorBueFlange Feature-Operating Temperatures-55°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HMM11DRKN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HMM11DRKN Payment Methods



HMM11DRKN Shipping Methods



If you have any question about HMM11DRKN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com