

## HMM18DSEF

## **HMM18DSEF** Information

Heisener.com	Part Number Manufacturer Category Description Package	HMM18DSEF Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 36POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **HMM18DSEF** Specifications

CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Nounting TypePanel MountYounder SpecifiedSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange Feature- Soldour Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Nounting TypePanel MountYounder SpecifiedSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange Feature- Soldour Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	HMM18DSEF	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorBueFlange Feature- 56°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSulf Sector (1.67µm)Contact TypeSulf Sector (1.67µm)Contact TypeSolym (0.76µm)Contact TypeSulf Sector (1.67µm)Contact TypeSulf Sector (1.67µm)Contact TypeSulf Sector (1.67µm)ColorBueFange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95µm) DiaOperating Temperature-55°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-Costact Schure-State Schure-ColorBueFeatures-Color-State Schure-Color-State Schure-State Schure <td>Series</td> <td>-</td> <td></td>	Series	-	
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 36   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Panel Mount   Termination Solder Eyelet(s)   Contact Material Beryllium Copper   Contact Finish Gold   Contact Type Full Bellows   Color Bue   Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	18	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 125°C	Number of Positions	36	
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBheFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Panel Mount	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)	
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper	
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlueFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue	
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	
Report errors	Operating Temperature	-65°C ~ 125°C	
			Report errors?

#### **HMM18DSEF** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## HMM18DSEF Payment Methods



### HMM18DSEF Shipping Methods



If you have any question about HMM18DSEF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com