



HMM36DRKS Information

Heisener.com

Part Number HMM36DRKS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 72POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HMM36DRKS Specifications

Manufacturer Part Number HMM36DRKS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C Report errors?	•	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Type Full Bellows Cotact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	HMM36DRKS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness $0.062" (1.57mm)$ Number of Rows2Pitch $0.156" (3.96mm)$ Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature $-65°C \sim 125°C$	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness $0.062" (1.57mm)$ Number of Rows2Pitch $0.156" (3.96mm)$ Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature $-65°C \sim 125°C$		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Cotact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	36
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	72
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 125 °C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 30μ in $(0.76\mu$ m)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 125 °C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Beryllium Copper
Contact Type Full Bellows Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Blue Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HMM36DRKS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HMM36DRKS Payment Methods



















HMM36DRKS Shipping Methods













If you have any question about HMM36DRKS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com