



### **HP2-DC24V Information**

Heisener.com

Part Number HP2-DC24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HP2-DC24V Specifications**

Manufacturer Part Number         HP2-DC24V           Manufacturer         Panasonic Electric Works           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         HP           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         54.5mA           Coil Voltage         24VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC - Nom           Turn On Voltage (Max)         19.2 VDC           Turn Off Voltage (Min)         3.6 VDC           Operate Time         25ms           Release Time         25ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.205" (5.2mm)    Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesHPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current54.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.205" (5.2mm)	Manufacturer Part Number	HP2-DC24V
Package - Series HP Relay Type General Purpose Coil Type Non Latching Coil Current 54.5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Manufacturer	Panasonic Electric Works
Package - Beries HP General Purpose General Purpose Non Latching St. 54.5mA St. 54.5mB S	Category	Relays
SeriesHPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current54.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.205" (5.2mm)		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 54.5mA  Coil Voltage 24VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 25ms  Release Time 25ms  Features  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Package	-
Coil TypeNon LatchingCoil Current54.5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.205" (5.2mm)	Series	НР
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 25ms Release Time 25ms Features	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 25ms  Release Time 25ms  Release Time - 25ms  Features - Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Coil Current	54.5mA
Contact Rating (Current)  Switching Voltage  250VAC - Nom  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  10A  250VAC - Nom  19.2 VDC  25ms  50 VDC  25ms  Plug In, Quick Connect - 0.205" (5.2mm)	Coil Voltage	24VDC
Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 25ms  Release Time 25ms  Features -  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  19.2 VDC  3.6 VDC  25ms  Plug In, Quick Connect - 0.205" (5.2mm)	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.205" (5.2mm)	Switching Voltage	250VAC - Nom
Operate Time 25ms  Release Time 25ms  Features -  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Turn On Voltage (Max)	19.2 VDC
Release Time 25ms  Features - Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Turn Off Voltage (Min)	3.6 VDC
Features -  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Operate Time	25ms
Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Release Time	25ms
Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.205" (5.2mm)
		Report errors?

#### **HP2-DC24V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HP2-DC24V Payment Methods**



















## **HP2-DC24V Shipping Methods**













If you have any question about HP2-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com