



HP4-AC220V Information

Heisener.com

Part Number HP4-AC220V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 10A 220V

Package -


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number HP4-AC220V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series HP Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)		
Category Relays Power Relays, Over 2 Amps Package - Series HP Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 220V AC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250V AC - Nom Turn On Voltage (Max) 176 V AC Turn Off Voltage (Min) 66 V AC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Manufacturer Part Number	HP4-AC220V
Package - Series HP Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Manufacturer	Panasonic Electric Works
Package - Series HP Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 220V AC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250V AC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Category	Relays
SeriesHPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - NomTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.205" (5.2mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Package	-
Coil TypeNon LatchingCoil Current21mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - NomTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.205" (5.2mm)	Series	HP
Coil Current21mACoil Voltage220VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - NomTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.205" (5.2mm)	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Coil Current	21mA
Contact Rating (Current) Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style 10A 250VAC - Nom 176 VAC 176 VAC 30ms 66 VAC 30ms Plug In, Quick Connect - 0.205" (5.2mm)	Coil Voltage	220VAC
Switching Voltage 250VAC - Nom Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style 176 VAC	Contact Rating (Current)	10A
Turn Off Voltage (Min) 66 VAC Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Switching Voltage	250VAC - Nom
Operate Time 30ms Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Turn On Voltage (Max)	176 VAC
Release Time 30ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Turn Off Voltage (Min)	66 VAC
Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Release Time	30ms
Termination Style Plug In, Quick Connect - 0.205" (5.2mm)	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.205" (5.2mm)
Report errors.		Report errors?

HP4-AC220V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HP4-AC220V Payment Methods



















HP4-AC220V Shipping Methods













If you have any question about HP4-AC220V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com