



HPA100X2DA Information

Heisener.com

Part Number HPA100X2DA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BAROMETER Package Module Cube

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HPA100X2DA Specifications

Manufacturer Part Number HPA100X2DA Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type RS-232 Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageModule CubeSeries-Pressure TypeAbsoluteOperating Pressure17.6 PSI (121.35 kPa)Output TypeRS-232Output-Accuracy±0.06%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	HPA100X2DA
Package Module Cube Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type RS-232 Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package Module Cube Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type RS-232 Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Category	Sensors, Transducers
Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type RS-232 Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure17.6 PSI (121.35 kPa)Output TypeRS-232Output-Accuracy±0.06%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Package	Module Cube
Operating Pressure 17.6 PSI (121.35 kPa) Output Type RS-232 Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Series	-
Output Type RS-232 Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Pressure Type	Absolute
Output - Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Connector Maximum Pressure - Connector Maximum Pressure - 40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Operating Pressure	17.6 PSI (121.35 kPa)
Accuracy ±0.06% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Connector Maximum Pressure - Coperating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Output Type	RS-232
Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - - - - - - - - - - - - -	Output	-
Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Accuracy	$\pm 0.06\%$
Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Connector Maximum Pressure - Coperating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Connector	Port Size	Female - 1/8" (3.18mm) Swagelok?
Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

HPA100X2DA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HPA100X2DA Payment Methods





















HPA100X2DA Shipping Methods













If you have any question about HPA100X2DA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com