



HPA200XTTA Information

Heisener.com

Part Number HPA200XTTA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BAROMETER Package Module Cube

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HPA200XTTA Specifications

Manufacturer Part Number HPA200XTTA Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type TTL Output - Accuracy ±0.03% Voltage - Supply 6 V ~ 26 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		
Category Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type TTL Output - Accuracy ±0.03% Voltage - Supply 6 V ~ 26 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Manufacturer Part Number	HPA200XTTA
Package Module Cube Series - Pressure Type Absolute Operating Pressure 17.6 PSI (121.35 kPa) Output Type TTL Output - Accuracy ±0.03% Voltage - Supply 6 V ~ 26 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeAbsoluteOperating Pressure17.6 PSI (121.35 kPa)Output TypeTTLOutput-Accuracy±0.03%Voltage - Supply6 V ~ 26 VPort SizeFemale - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule Cube	Category	Sensors, Transducers
Series - Absolute Operating Pressure Operating Pressure Output Type TTL Output Accuracy +0.03% Voltage - Supply Female - 1/8" (3.18mm) Swagelok? Port Style Females - Termination Style Maximum Pressure Operating Temperature -40°C ~ 85°C Package / Case Module Cube		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure17.6 PSI (121.35 kPa)Output TypeTTLOutput-Accuracy±0.03%Voltage - Supply6 V ~ 26 VPort SizeFemale - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule Cube	Package	Module Cube
Operating Pressure 17.6 PSI (121.35 kPa) Output Type TTL Output - Accuracy ±0.03% Voltage - Supply 6 V ~ 26 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Series	-
Output Type TTL Output - Accuracy ±0.03% Voltage - Supply 6 V ~ 26 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Pressure Type	Absolute
Output - Accuracy ±0.03% Voltage - Supply 6 V ~ 26 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Operating Pressure	17.6 PSI (121.35 kPa)
Accuracy $\pm 0.03\%$ Voltage - Supply $6 \text{ V} \sim 26 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule Cube	Output Type	TTL
Voltage - Supply $6 \text{ V} \sim 26 \text{ V}$ Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Connector Maximum Pressure - Connector Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Output	-
Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Connector Maximum Pressure - Coperating Temperature -40°C ~ 85°C Package / Case Module Cube	Accuracy	±0.03%
Port Style Threaded Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Voltage - Supply	6 V ~ 26 V
Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Port Size	Female - 1/8" (3.18mm) Swagelok?
Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule Cube	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Termination Style	Connector
Package / Case Module Cube	Maximum Pressure	-
	Operating Temperature	-40°C ~ 85°C
Supplier Device Package -	Package / Case	Module Cube
THE TOTAL OF THE T	Supplier Device Package	-
Report errors?		Report errors?

HPA200XTTA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HPA200XTTA Payment Methods





















HPA200XTTA Shipping Methods













If you have any question about HPA200XTTA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com