



### **HPB100WTTA Information**

Heisener.com

Part Number HPB100WTTA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description BAROMETER** Package Module Cube

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HPB100WTTA Specifications**

Manufacturer Part Number       HPB100WTTA         Manufacturer       Honeywell Microelectronics & Precision Sensors         Category       Sensors, Transducers         Package       Module Cube         Series       -         Pressure Type       Absolute         Operating Pressure       7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)         Output Type       TTL         Output       -         Accuracy       ±0.012 PSI (±0.08 kPa)         Voltage - Supply       6 V ~ 26 V         Port Size       Male - 0.13" (3.18mm) Tube         Port Style       Barbed         Features       -         Termination Style       Connector         Maximum Pressure       -         Operating Temperature       -40°C ~ 85°C		
Category Sensors, Transducers Pressure Sensors, Transducers  Package Module Cube Series - Pressure Type Absolute Operating Pressure 7,25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type TTL Output - Accuracy +0.012 PSI (±0.08 kPa) Voltage - Supply 6 V ~ 26 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Maximum Pressure - Connector Maximum Pressure	Manufacturer Part Number	HPB100WTTA
Package Module Cube Series - Pressure Type Absolute Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type TTL Output Type TTL Output - Accuracy ±0.012 PSI (±0.08 kPa) Voltage - Supply 6 V ~ 26 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure -	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeAbsoluteOperating Pressure7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)Output TypeTTLOutput-Accuracy±0.012 PSI (±0.08 kPa)Voltage - Supply6 V ~ 26 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-	Category	Sensors, Transducers
Series         -           Pressure Type         Absolute           Operating Pressure         7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)           Output Type         TTL           Output         -           Accuracy         ±0.012 PSI (±0.08 kPa)           Voltage - Supply         6 V ~ 26 V           Port Size         Male - 0.13" (3.18mm) Tube           Port Style         Barbed           Features         -           Termination Style         Connector           Maximum Pressure         -		Pressure Sensors, Transducers
Pressure Type Absolute  Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)  Output Type TTL  Output -  Accuracy ±0.012 PSI (±0.08 kPa)  Voltage - Supply 6 V ~ 26 V  Port Size Male - 0.13" (3.18mm) Tube  Port Style Barbed  Features -  Termination Style Connector  Maximum Pressure -	Package	Module Cube
Operating Pressure         7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)           Output Type         TTL           Output         -           Accuracy         ±0.012 PSI (±0.08 kPa)           Voltage - Supply         6 V ~ 26 V           Port Size         Male - 0.13" (3.18mm) Tube           Port Style         Barbed           Features         -           Termination Style         Connector           Maximum Pressure         -	Series	-
Output TypeTTLOutput-Accuracy±0.012 PSI (±0.08 kPa)Voltage - Supply6 V ~ 26 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-	Pressure Type	Absolute
Output - Accuracy $\pm 0.012 \text{ PSI } (\pm 0.08 \text{ kPa})$ Voltage - Supply $6 \text{ V} \sim 26 \text{ V}$ Port Size Male - $0.13$ " ( $3.18 \text{mm}$ ) Tube Port Style Barbed Features - Connector Maximum Pressure	Operating Pressure	7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)
Accuracy $\pm 0.012$ PSI ( $\pm 0.08$ kPa)Voltage - Supply $6 \text{ V} \sim 26 \text{ V}$ Port SizeMale - $0.13$ " ( $3.18$ mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-	Output Type	TTL
Voltage - Supply $6 \text{ V} \sim 26 \text{ V}$ Port SizeMale - $0.13$ " ( $3.18$ mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-	Output	-
Port Size Male - 0.13" (3.18mm) Tube  Port Style Barbed  Features -  Termination Style Connector  Maximum Pressure -	Accuracy	±0.012 PSI (±0.08 kPa)
Port Style Barbed Features - Termination Style Connector Maximum Pressure -	Voltage - Supply	6 V ~ 26 V
Features - Termination Style Connector Maximum Pressure -	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style Connector  Maximum Pressure -	Port Style	Barbed
Maximum Pressure -	Features	-
	Termination Style	Connector
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Maximum Pressure	-
operating temperature	Operating Temperature	-40°C ~ 85°C
Package / Case Module Cube	Package / Case	Module Cube
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

#### **HPB100WTTA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HPB100WTTA Payment Methods**



















## **HPB100WTTA Shipping Methods**













If you have any question about HPB100WTTA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com