



HPB200W2DA Information

Heisener.com

Part Number HPB200W2DA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BAROMETER Package Module Cube

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HPB200W2DA Specifications

Manufacturer Part NumberHPB200W2DAManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubeSeries-Pressure TypeAbsoluteOperating Pressure7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)Output TypeRS-232Output-Accuracy±0.006 PSI (±0.04 kPa)Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		
Category Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type RS-232 Output - Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer Part Number	HPB200W2DA
Package Module Cube Series - Pressure Type Absolute Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type RS-232 Output - Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package Module Cube Series - Pressure Type Absolute Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type RS-232 Output - Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Category	Sensors, Transducers
Series - Pressure Type Absolute Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type RS-232 Output - Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)Output TypeRS-232Output-Accuracy±0.006 PSI (±0.04 kPa)Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Package	Module Cube
Operating Pressure 7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa) Output Type RS-232 Output - Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package - Module Cube	Series	-
Output TypeRS-232Output-Accuracy±0.006 PSI (±0.04 kPa)Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Pressure Type	Absolute
Output - Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Operating Pressure	7.25 PSI ~ 17.4 PSI (50 kPa ~ 120 kPa)
Accuracy ±0.006 PSI (±0.04 kPa) Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Connector Maximum Pressure - Coperating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Output Type	RS-232
Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) TubePort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output	-
Port Size Male - 0.13" (3.18mm) Tube Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	±0.006 PSI (±0.04 kPa)
Port Style Barbed Features - Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Connector Maximum Pressure - Coperating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Connector	Port Size	Male - 0.13" (3.18mm) Tube
Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Barbed
Maximum Pressure-Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
	Supplier Device Package	-
Report errors?		Report errors?

HPB200W2DA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HPB200W2DA Payment Methods



















HPB200W2DA Shipping Methods













If you have any question about HPB200W2DA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com