



HPG1105W-TR Information



For Reference Only

Part Number HPG1105W-TR
Manufacturer Stanley Electric Co
Category Optoelectronics

LED Indication - Discrete

Description LED GREEN CLEAR 1206 SMD

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HPG1105W-TR Specifications

Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series 1105W Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W	-	
Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series 1105W Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Manufacturer Part Number	HPG1105W-TR
Package 1206 (3216 Metric) Series 1105W Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Manufacturer	Stanley Electric Co
Package 1206 (3216 Metric) Series 1105W Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Category	Optoelectronics
Series 1105W Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm		LED Indication - Discrete
Color Green Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Package	1206 (3216 Metric)
Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Series	1105W
Lens ColorColorlessLens TransparencyClearMillicandela Rating30mcdLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)2.1VCurrent - Test20mAViewing Angle40°Mounting TypeSurface MountWavelength - Dominant567nmWavelength - Peak560nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3216 TypeSize / Dimension3.20mm L x 1.60mm WHeight (Max)2.05mm	Color	Green
Lens Transparency Millicandela Rating 30mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle Mounting Type Surface Mount Wavelength - Dominant Wavelength - Peak Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W Height (Max) Clear Round Round Round Surface Round Surface Round Surface Round Surface Round Surface Surfa	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Lens Color	Colorless
Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) 2.1V Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Millicandela Rating	30mcd
Current - Test 20mA Viewing Angle 40° Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Lens Style/Size	Round with Domed Top, 1.60mm
Viewing Angle 40° Mounting TypeSurface MountWavelength - Dominant 567nm Wavelength - Peak 560nm Features-Package / Case $1206 (3216 \text{ Metric})$ Supplier Device Package 3216 Type Size / Dimension $3.20 \text{mm L x 1.60 mm W}$ Height (Max) 2.05mm	Voltage - Forward (Vf) (Typ)	2.1V
Mounting Type Surface Mount Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Current - Test	20mA
Wavelength - Dominant 567nm Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Viewing Angle	40°
Wavelength - Peak 560nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Mounting Type	Surface Mount
Features - Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Wavelength - Dominant	567nm
Package / Case 1206 (3216 Metric) Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Wavelength - Peak	560nm
Supplier Device Package 3216 Type Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Features	-
Size / Dimension 3.20mm L x 1.60mm W Height (Max) 2.05mm	Package / Case	1206 (3216 Metric)
Height (Max) 2.05mm	Supplier Device Package	3216 Type
	Size / Dimension	3.20mm L x 1.60mm W
Report errors?	Height (Max)	2.05mm
		Report errors?

HPG1105W-TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HPG1105W-TR Payment Methods



















HPG1105W-TR Shipping Methods













If you have any question about HPG1105W-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com