



HPX015GD Information

Heisener.com

Part Number HPX015GD

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE UNAMP 0-15PSI

6-DIP Module **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HPX015GD Specifications

Manufacturer Part Number HPX015GD Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 6-DIP Module Series HPX Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 42 mV (3V) Accuracy ±0.3% Voltage - Supply 3 V ~ 10 V Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -		
CategorySensors, TransducersPackage6-DIP ModuleSeriesHPXPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 42 mV (3V)Accuracy±0.3%Voltage - Supply3 V ~ 10 VPort SizeMale - 0.1" (2.49mm) TubePort StyleBarblessFeatures-Termination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Manufacturer Part Number	HPX015GD
Package 6-DIP Module Series HPX Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Wheatstone Bridge Output 0 mV ~ 42 mV (3V) Accuracy ±0.3% Voltage - Supply 3 V ~ 10 V Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features Feat	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-DIP ModuleSeriesHPXPressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 42 mV (3V)Accuracy±0.3%Voltage - Supply3 V ~ 10 VPort SizeMale - 0.1" (2.49mm) TubePort StyleBarblessFeatures-Termination StylePCBMaximum Pressure45 PSI (310.26 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Category	Sensors, Transducers
Series HPX Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 42 mV (3V) Accuracy ±0.3% Voltage - Supply 3 V ~ 10 V Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 15 PSI (103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 42 mV (3V) Accuracy ±0.3% Voltage - Supply 3 V ~ 10 V Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Package	6-DIP Module
Operating Pressure Output Type Wheatstone Bridge Output Output OnV ~ 42 mV (3V) Accuracy ±0.3% Voltage - Supply Style Port Size Male - 0.1" (2.49mm) Tube Barbless Features Features Features Features PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature Package / Case Supplier Device Package 15 PSI (103.42 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge A v (3V) Wheatstone Bridge ### 103.42 mV (3V) ### 2 mV (3V) ### 103.42 mV (3V) ### 103.	Series	HPX
Output Type Output Outp	Pressure Type	Vented Gauge
Output $0 \text{ mV} \sim 42 \text{ mV} (3\text{V})$ Accuracy $\pm 0.3\%$ Voltage - Supply $3 \text{ V} \sim 10 \text{ V}$ Port Size $\text{Male - 0.1" (2.49 \text{mm}) Tube}}$ Port Style $\text{Barbless}}$ Features - Termination Style PCB Maximum Pressure $45 \text{ PSI (310.26 kPa)}$ Operating Temperature $-20^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Package / Case 6-DIP Module Supplier Device Package $-$	Operating Pressure	15 PSI (103.42 kPa)
Accuracy ±0.3% Voltage - Supply 3 V ~ 10 V Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features - Termination Style Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package	Output	$0 \text{ mV} \sim 42 \text{ mV} (3\text{V})$
Port Size Male - 0.1" (2.49mm) Tube Port Style Barbless Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Accuracy	±0.3%
Port Style Barbless Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Voltage - Supply	3 V ~ 10 V
Features - Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Port Size	Male - 0.1" (2.49mm) Tube
Termination Style PCB Maximum Pressure 45 PSI (310.26 kPa) Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Port Style	Barbless
Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-20°C ~ 100°CPackage / Case6-DIP ModuleSupplier Device Package-	Features	-
Operating Temperature -20°C ~ 100°C Package / Case 6-DIP Module Supplier Device Package -	Termination Style	PCB
Package / Case 6-DIP Module Supplier Device Package -	Maximum Pressure	45 PSI (310.26 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 100°C
	Package / Case	6-DIP Module
Report errors?	Supplier Device Package	-
		Report errors?

HPX015GD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HPX015GD Payment Methods





















HPX015GD Shipping Methods













If you have any question about HPX015GD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com