



# HR212-10R-8SD(72) Information

Heisener.com

Part NumberHR212-10R-8SD(72)ManufacturerHirose Electric Co LtdCategoryConnectors, Interconnects<br/>Circular Connectors

**Description** CONN RECEPT 8POS VERT GOLD SAND

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## HR212-10R-8SD(72) Specifications

| Manufacturer Part Number     HR212-10R-8SD(72)       Manufacturer     Hirose Electric Co Ltd       Category     Connectors, Interconnects       Package     -       Series     HR212       Connector Type     Receptacle, Female Sockets       Number of Positions     8       Shell Size - Insert     10       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange; Through Hole       Termination     Solder       Fastening Type     Push-Pull       Orientation     Keyed       Ingress Protection     -       Shell Material, Finish     Brass and Zinc, Nickel Plated       Contact Finish     Tin       Features     Shielded       Voltage - Rated     100VAC       Current Rating     1A   |                          |                                   |
|---|--------------------------|-----------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesHR212Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A   | Manufacturer Part Number | HR212-10R-8SD(72)                 |
| Package-SeriesHR212Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A  | Manufacturer             | Hirose Electric Co Ltd            |
| Package-SeriesHR212Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A  | Category                 | Connectors, Interconnects         |
| SeriesHR212Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A  |                          | Circular Connectors               |
| Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A   | Package                  | -                                 |
| Number of Positions8Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A   | Series                   | HR212                             |
| Shell Size - Insert10Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A   | Connector Type           | Receptacle, Female Sockets        |
| Shell Size, MIL  Mounting Type Panel Mount, Flange; Through Hole  Termination Solder  Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Brass and Zinc, Nickel Plated  Contact Finish Tin  Features Shielded  Voltage - Rated 100VAC Current Rating 1-   | Number of Positions      | 8                                 |
| Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishBrass and Zinc, Nickel PlatedContact FinishTinFeaturesShieldedVoltage - Rated100VACCurrent Rating1A  | Shell Size - Insert      | 10                                |
| Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Brass and Zinc, Nickel Plated Contact Finish Tin Features Shielded Voltage - Rated 100VAC Current Rating 1A   | Shell Size, MIL          | -                                 |
| Fastening Type Orientation Keyed Ingress Protection Shell Material, Finish Contact Finish Tin Features Shielded Voltage - Rated Current Rating Push-Pull Keyed  Keyed  Feyed Feyed Fasted From Strong | Mounting Type            | Panel Mount, Flange; Through Hole |
| Orientation Keyed Ingress Protection - Shell Material, Finish Brass and Zinc, Nickel Plated Contact Finish Tin Features Shielded Voltage - Rated 100VAC Current Rating 1A   | Termination              | Solder                            |
| Ingress Protection - Shell Material, Finish Brass and Zinc, Nickel Plated Contact Finish Tin Features Shielded Voltage - Rated 100VAC Current Rating 1A   | Fastening Type           | Push-Pull                         |
| Shell Material, Finish Contact Finish Tin Features Shielded Voltage - Rated Current Rating 1A Brass and Zinc, Nickel Plated Tin Current Rating Tin Shielded 100VAC  | Orientation              | Keyed                             |
| Contact Finish Features Shielded Voltage - Rated Current Rating 1A  | Ingress Protection       | -                                 |
| Features Shielded  Voltage - Rated 100VAC  Current Rating 1A  | Shell Material, Finish   | Brass and Zinc, Nickel Plated     |
| Voltage - Rated 100VAC Current Rating 1A  | Contact Finish           | Tin                               |
| Current Rating 1A   | Features                 | Shielded                          |
|   | Voltage - Rated          | 100VAC                            |
| Report errors?  | Current Rating           | 1A                                |
|   |                          | Report errors?                    |

### HR212-10R-8SD(72) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### HR212-10R-8SD(72) Payment Methods



















## HR212-10R-8SD(72) Shipping Methods













If you have any question about HR212-10R-8SD(72), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com