

HR30-6JA-6P(71)

HR30-6JA-6P(71) Information

www.hakener.com	Part Number Manufacturer Category Description Package	HR30-6JA-6P(71) Hirose Electric Co Ltd Connectors, Interconnects Circular Connectors CONN JACK 6POS MALE SOLDER - For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HR30-6JA-6P(71) Specifications

ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsPackage-Package-SeriesHR30Connector TypeJack, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationFree Jourt Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrian ReliefVoltage - Rated100VAC, 140VDC		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Package-SeriesHR30Connector TypeJack, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionPolyphenylene Sulfide (PPS)Shell Material, FinishGoldFeaturesStrian ReliefVoltage - RatedJOVAC, 140VDCCurrent Rating2A	Manufacturer Part Number	HR30-6JA-6P(71)
Circular ConnectorsPackage-SeriesHR30Connector TypeJack, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionPolyphenylene Sulfide (PPS)Shell Material, FinishGoldFeaturesStrain ReliefVoltage - RatedJOVAC, 140VDCCurrent Rating2A	Manufacturer	Hirose Electric Co Ltd
Package-SeriesHR30Connector TypeJack, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionFor Joust Tight, WaterproofShell Material, FinishOlyphenylene Sulfide (PPS)FeaturesGoldVoltage - Rated100VAC, 140VDCCurrent Rating2A	Category	Connectors, Interconnects
SeriesHR30Connector TypeJack, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishSolder CupFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A		Circular Connectors
Connector TypeJack, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionPlo7 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Package	-
Number of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishStrain ReliefFeatures100VAC, 140VDCVoltage - Rated2A	Series	HR30
Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Connector Type	Jack, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Shell Size - Insert	6
TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Shell Size, MIL	-
Fastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Termination	Solder Cup
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Fastening Type	Push-Pull
Shell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Orientation	Keyed
Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Ingress Protection	IP67 - Dust Tight, Waterproof
FeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Shell Material, Finish	Polyphenylene Sulfide (PPS)
Voltage - Rated100VAC, 140VDCCurrent Rating2A	Contact Finish	Gold
Current Rating 2A	Features	Strain Relief
	Voltage - Rated	100VAC, 140VDC
Report errors?	Current Rating	2A
		Report errors?

HR30-6JA-6P(71) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HR30-6JA-6P(71) Payment Methods



HR30-6JA-6P(71) Shipping Methods



If you have any question about HR30-6JA-6P(71), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com