



HR30-6PB-6P Information



For Reference Only

Part Number HR30-6PB-6P

Manufacturer Hirose Electric Co Ltd

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 6POS MALE SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HR30-6PB-6P Specifications

Manufacturer Part NumberHR30-6PB-6PManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsPackage-SeriesHR30Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesHR30Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Manufacturer Part Number	HR30-6PB-6P
Package-SeriesHR30Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Manufacturer	Hirose Electric Co Ltd
Package-SeriesHR30Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Category	Connectors, Interconnects
SeriesHR30Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Package	-
Number of Positions Shell Size - Insert 6 Shell Size, MIL	Series	HR30
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishPolyphenylene Sulfide (PPS)Contact FinishGoldFeaturesStrain ReliefVoltage - Rated100VAC, 140VDCCurrent Rating2A	Shell Size - Insert	6
Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Polyphenylene Sulfide (PPS) Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Orientation	Keyed
Contact Finish Gold Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 100VAC, 140VDC Current Rating 2A	Shell Material, Finish	Polyphenylene Sulfide (PPS)
Voltage - Rated 100VAC, 140VDC Current Rating 2A	Contact Finish	Gold
Current Rating 2A	Features	Strain Relief
	Voltage - Rated	100VAC, 140VDC
Report errors?	Current Rating	2A
		Report errors?

HR30-6PB-6P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HR30-6PB-6P Payment Methods





















HR30-6PB-6P Shipping Methods













If you have any question about HR30-6PB-6P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com