



HS10 100R J Information

For Reference Only

Part Number HS10 100R J Manufacturer Ohmite

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 100 OHM 5% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS10 100R J Specifications

Manufacturer Part NumberHS10 100R JManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.626" L x 0.335" W (15.90mm x 8.50mm)Height - Seated (Max)0.346" (8.80mm)Lead StyleSolder Lugs		
CategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.626" L x 0.335" W (15.90mm x 8.50mm)Height - Seated (Max)0.346" (8.80mm)Lead StyleSolder Lugs	Manufacturer Part Number	HS10 100R J
Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 100 Ohms Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.626" L x 0.335" W (15.90mm x 8.50mm)Height - Seated (Max)0.346" (8.80mm)Lead StyleSolder Lugs	Category	Resistors
SeriesARCOL, HSResistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.626" L x 0.335" W (15.90mm x 8.50mm)Height - Seated (Max)0.346" (8.80mm)Lead StyleSolder Lugs		Chassis Mount Resistors
Resistance100 OhmsTolerance±5%Power (Watts)10WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.626" L x 0.335" W (15.90mm x 8.50mm)Height - Seated (Max)0.346" (8.80mm)Lead StyleSolder Lugs	Package	Axial, Box
Tolerance ±5% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension Height - Seated (Max) Lead Style 10W Wirewound ±100ppm/°C - Read Silve - 0.626" L x 0.335" W (15.90mm x 8.50mm) 0.346" (8.80mm) Lead Style	Resistance	100 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.626" L x 0.335" W (15.90mm x 8.50mm)Height - Seated (Max)0.346" (8.80mm)Lead StyleSolder Lugs	Tolerance	±5%
Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Power (Watts)	10W
Operating Temperature Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Temperature Coefficient	$\pm 100 ppm/^{\circ}C$
Coating, Housing Type Mounting Feature Flanges Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Operating Temperature	-
Mounting Feature Size / Dimension O.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) Lead Style Solder Lugs	Features	-
Size / Dimension 0.626" L x 0.335" W (15.90mm x 8.50mm) Height - Seated (Max) 0.346" (8.80mm) Lead Style Solder Lugs	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style 0.346" (8.80mm) Solder Lugs	Mounting Feature	Flanges
Lead Style Solder Lugs	Size / Dimension	0.626" L x 0.335" W (15.90mm x 8.50mm)
	Height - Seated (Max)	0.346" (8.80mm)
	Lead Style	Solder Lugs
Package / Case Axial, Box	Package / Case	Axial, Box
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

HS10 100R J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS10 100R J Payment Methods



















HS10 100R J Shipping Methods













If you have any question about HS10 100R J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com