



HS100 11K F Information



For Reference Only

Part Number HS100 11K F

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 11K OHM 1% 100W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS100 11K F Specifications

Manufacturer Part Number HS100 11K F Manufacturer Ohmite Category Resistors Package Axial, Box Series ARCOL, HS Resistance 11 kOhms Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 11 kOhms Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer Part Number	HS100 11K F
Chassis Mount Resistors Axial, Box Series ARCOL, HS Resistance 11 kOhms Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension Lead Style Solder Lugs Package / Case Axial, Box Failure Rate ARCOL, HS Axial, Box Axial, Box Axial, Box Axial, Box ARCOL, HS Axial, Box Axial, Box Axial, Box ARCOL, HS Axial, Box Axial, Box Axial, Box	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance11 kOhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance11 kOhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance 11 kOhms Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	11 kOhms
Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±1%
Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	100W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±25ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	2.566" L x 1.075" W (65.20mm x 27.30mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.949" (24.10mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HS100 11K F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS100 11K F Payment Methods



















HS100 11K F Shipping Methods













If you have any question about HS100 11K F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com