



HS100 3K9 F Information



For Reference Only

Part Number HS100 3K9 F

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 3.9K OHM 1% 100W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS100 3K9 F Specifications

Manufacturer Part Number Manufacturer Ohmite Category Resistors Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 3.9 kOhms Tolerance ±1% Power (Watts) Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature Features Coating, Housing Type Aluminum Manusting Features Flances
CategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance3.9 kOhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminum
Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 3.9 kOhms Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature Features - Coating, Housing Type Aluminum
PackageAxial, BoxSeriesARCOL, HSResistance3.9 kOhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminum
SeriesARCOL, HSResistance3.9 kOhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminum
Resistance3.9 kOhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminum
Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum
Power (Watts) Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum
Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum
Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum
Operating Temperature - Features - Coating, Housing Type Aluminum
Features - Coating, Housing Type Aluminum
Coating, Housing Type Aluminum
Mounting Foothing
Mounting Feature Flanges
Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm)
Height - Seated (Max) 0.949" (24.10mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate -
Report errors?

HS100 3K9 F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS100 3K9 F Payment Methods



















HS100 3K9 F Shipping Methods













If you have any question about HS100 3K9 F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com