

## **HS100 4K7 J Information**



For Reference Only

Part Number HS100 4K7 J

Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 4.7K OHM 5% 100W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HS100 4K7 J Specifications**

Manufacturer Part Number         HS100 4K7 J           Manufacturer         Ohmite           Category         Resistors           Package         Axial, Box           Series         ARCOL, HS           Resistance         4.7 kOhms           Tolerance         ±5%           Power (Watts)         100W           Composition         Wirewound           Temperature Coefficient         ±25ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         2.566" L x 1.075" W (65.20mm x 27.30mm)           Height - Seated (Max)         0.949" (24.10mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -		
CategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance4.7 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	HS100 4K7 J
Chassis Mount Resistors           Package         Axial, Box           Series         ARCOL, HS           Resistance         4.7 kOhms           Tolerance         ±5%           Power (Watts)         100W           Composition         Wirewound           Temperature Coefficient         ±25ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         2.566" L x 1.075" W (65.20mm x 27.30mm)           Height - Seated (Max)         0.949" (24.10mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -	Manufacturer	Ohmite
Package         Axial, Box           Series         ARCOL, HS           Resistance         4.7 kOhms           Tolerance         ±5%           Power (Watts)         100W           Composition         Wirewound           Temperature Coefficient         ±25ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         2.566" L x 1.075" W (65.20mm x 27.30mm)           Height - Seated (Max)         0.949" (24.10mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -	Category	Resistors
Series         ARCOL, HS           Resistance         4.7 kOhms           Tolerance         ±5%           Power (Watts)         100W           Composition         Wirewound           Temperature Coefficient         ±25ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         2.566" L x 1.075" W (65.20mm x 27.30mm)           Height - Seated (Max)         0.949" (24.10mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -		Chassis Mount Resistors
Resistance4.7 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±5%  Power (Watts) 100W  Composition Wirewound  Temperature Coefficient ±25ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm)  Height - Seated (Max) 0.949" (24.10mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Series	ARCOL, HS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±25ppm/°C  Operating Temperature  - Features  - Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  Lead Style  Package / Case  Failure Rate  100W  Wirewound  ±25ppm/°C  -  -  -  -  0-  10-  10-  10-  10-  1	Resistance	4.7 kOhms
Composition Wirewound  Temperature Coefficient ±25ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm)  Height - Seated (Max) 0.949" (24.10mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±25ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm)  Height - Seated (Max) 0.949" (24.10mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Power (Watts)	100W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm)  Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±25ppm/°C
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  2.566" L x 1.075" W (65.20mm x 27.30mm)  Height - Seated (Max)  0.949" (24.10mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Operating Temperature	-
Mounting Feature  Size / Dimension  2.566" L x 1.075" W (65.20mm x 27.30mm)  Height - Seated (Max)  0.949" (24.10mm)  Lead Style  Package / Case  Axial, Box  Failure Rate  -	Features	-
Size / Dimension 2.566" L x 1.075" W (65.20mm x 27.30mm)  Height - Seated (Max) 0.949" (24.10mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	2.566" L x 1.075" W (65.20mm x 27.30mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.949" (24.10mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

#### HS100 4K7 J Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HS100 4K7 J Payment Methods**





















## **HS100 4K7 J Shipping Methods**













If you have any question about HS100 4K7 J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com