

HS100 680R F

HS100 680R F Information

For Reference Only	Part Number Manufacturer	Ohmite	
	Category Description	Resistors Chassis Mount Resistors RES CHAS MNT 680 OHM 1% 100W	
	Package	Axial, Box	- HERRIGAN FERRISA
		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HS100 680R F Specifications

Manufacturer Ohmite Category Resistors Chassis Mount Resistors Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 680 Ohms Tolerance ±1% Power (Watts) 100W Composition Wirewound Toleparture Coefficient ±100pm/°C Operating Temperature - Operating Temperature - Coating, Housing Type Aluminum Size / Dimension 2.566° L x 1.075° W (65.20mm x 27.30mm) Bight - Seated (Max) 0.949° (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box		
CategoryResistorsPackageChassis Mount ResistorsPackageAxial, BoxSeriesARCOL, HSResistance680 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTomperature Coefficient±100pm/°COperating Temperature-Features-Size / DimensionKinnumSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)Solder LugsPackage / Case-Failure RateSolder LugsFailure Rate-Failure Rate-Fa	Manufacturer Part Number	HS100 680R F
Chassis Mount ResistorsPackageAxial, BoxSeriesARCOL, HSResistance680 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance680 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting Feature5266" L x 1.075" W (65.20mm x 27.30mm)Size / Dimension506er L ussHeight - Seated (Max)Solder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance680 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)O.949" (24.10mm)Lead StyleSolder LugsPackage / Case-Failure Rate-		Chassis Mount Resistors
Resistance680 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Operating Temperature-Coating, Housing TypeAluminumMounting FeatureElangesSize / Dimension0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.949" (24.10mm) 27.30mm) 27.30mm)Height - Seated (Max)Solder LugsPackage / CaseAixia, BoxFeatures-	Series	ARCOL, HS
Power (Watts)100WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.949" (24.10mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFailure Rate-	Resistance	680 Ohms
CompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeaturesElangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFeature Rate-	Tolerance	$\pm 1\%$
Temperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Power (Watts)	100W
Operating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Composition	Wirewound
Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Temperature Coefficient	±100ppm/°C
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Operating Temperature	-
Mounting FeatureFlangesSize / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Features	-
Size / Dimension2.566" L x 1.075" W (65.20mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Coating, Housing Type	Aluminum
Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	2.566" L x 1.075" W (65.20mm x 27.30mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.949" (24.10mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
1		Report errors?

HS100 680R F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HS100 680R F Payment Methods



HS100 680R F Shipping Methods



If you have any question about HS100 680R F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com