



### **HS15 12R F Information**



For Reference Only

Part Number HS15 12R F
Manufacturer Ohmite
Category Resistors

Resistors Chassis Mount Resistors

**Description** RES CHAS MNT 12 OHM 1% 15W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HS15 12R F Specifications**

Manufacturer Part NumberHS15 12R FManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance12 OhmsTolerance±1%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, Box		
CategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance12 OhmsTolerance±1%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder Lugs	Manufacturer Part Number	HS15 12R F
Chassis Mount Resistors  Package Axial, Box  Series ARCOL, HS  Resistance 12 Ohms  Tolerance ±1%  Power (Watts) 15W  Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance12 OhmsTolerance±1%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder Lugs	Category	Resistors
Series ARCOL, HS Resistance 12 Ohms  Tolerance ±1%  Power (Watts) 15W  Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs		Chassis Mount Resistors
Resistance12 OhmsTolerance±1%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder Lugs	Package	Axial, Box
Tolerance ±1%  Power (Watts) 15W  Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs	Series	ARCOL, HS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±100ppm/°C  Operating Temperature  - Features  - Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max)  Lead Style  Solder Lugs	Resistance	12 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder Lugs	Tolerance	$\pm 1\%$
Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs	Power (Watts)	15W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs	Temperature Coefficient	±100ppm/°C
Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs	Operating Temperature	-
Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs	Features	-
Size / Dimension         0.783" L x 0.440" W (19.89mm x 11.20mm)           Height - Seated (Max)         0.433" (11.00mm)           Lead Style         Solder Lugs	Coating, Housing Type	Aluminum
Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs	Mounting Feature	Flanges
Lead Style Solder Lugs	Size / Dimension	0.783" L x 0.440" W (19.89mm x 11.20mm)
	Height - Seated (Max)	0.433" (11.00mm)
Package / Case Axial. Box	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

#### **HS15 12R F Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HS15 12R F Payment Methods**





















### **HS15 12R F Shipping Methods**













If you have any question about HS15 12R F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com