



HS15 500R J Information



For Reference Only

Part Number HS15 500R J Manufacturer Ohmite

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 500 OHM 5% 15W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS15 500R J Specifications

Manufacturer Part NumberHS15 500R JManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance500 OhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-Report errors?		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 500 Ohms Tolerance ±5% Power (Watts) 15W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer Part Number	HS15 500R J
Package Axial, Box Series ARCOL, HS Resistance 500 Ohms Tolerance ±5% Power (Watts) 15W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance500 OhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance500 OhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance500 OhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±5% Power (Watts) 15W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) Lead Style Package / Case Package / Case Failure Rate - 15W Awirewound ±100ppm/°C - 0.783" L x 0.440" W (19.89mm x 11.20mm) Solder Lugs Axial, Box Failure Rate	Resistance	500 Ohms
Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±5%
Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	15W
Operating Temperature Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±100ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate 0.433" (11.00mm) Solder Lugs -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.783" L x 0.440" W (19.89mm x 11.20mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.433" (11.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HS15 500R J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS15 500R J Payment Methods





















HS15 500R J Shipping Methods













If you have any question about HS15 500R J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com