

## **HS15 R68 J Information**



For Reference Only

Part Number HS15 R68 J Manufacturer Ohmite Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 0.68 OHM 5% 15W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HS15 R68 J Specifications**

Manufacturer Part NumberHS15 R68 JManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance680 mOhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		
Category         Resistors           Package         Axial, Box           Series         ARCOL, HS           Resistance         680 mOhms           Tolerance         ±5%           Power (Watts)         15W           Composition         Wirewound           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.783" L x 0.440" W (19.89mm x 11.20mm)           Height - Seated (Max)         0.433" (11.00mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -	Manufacturer Part Number	HS15 R68 J
Package         Axial, Box           Series         ARCOL, HS           Resistance         680 mOhms           Tolerance         ±5%           Power (Watts)         15W           Composition         Wirewound           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.783" L x 0.440" W (19.89mm x 11.20mm)           Height - Seated (Max)         0.433" (11.00mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance680 mOhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance680 mOhmsTolerance±5%Power (Watts)15WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.783" L x 0.440" W (19.89mm x 11.20mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance 680 mOhms Tolerance ±5% Power (Watts) 15W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±5%  Power (Watts) 15W  Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Series	ARCOL, HS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±100ppm/°C  Operating Temperature  -  Features  -  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Resistance	680 mOhms
Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Power (Watts)	15W
Operating Temperature  Features  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max)  0.433" (11.00mm)  Lead Style  Package / Case  Axial, Box  Failure Rate  -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm) Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±100ppm/°C
Coating, Housing Type  Mounting Feature  Flanges  Size / Dimension  0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max)  0.433" (11.00mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Operating Temperature	-
Mounting Feature  Size / Dimension  0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max)  0.433" (11.00mm)  Lead Style  Package / Case  Axial, Box  Failure Rate  -	Features	-
Size / Dimension 0.783" L x 0.440" W (19.89mm x 11.20mm)  Height - Seated (Max) 0.433" (11.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  0.433" (11.00mm)  Solder Lugs  -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.783" L x 0.440" W (19.89mm x 11.20mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.433" (11.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

#### **HS15 R68 J Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HS15 R68 J Payment Methods**



















## **HS15 R68 J Shipping Methods**













If you have any question about HS15 R68 J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com