

HS150 1KF Information



For Reference Only

Part Number HS150 1KF
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1K OHM 1% 150W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS150 1KF Specifications

Manufacturer Part NumberHS150 1KFManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance1 kOhmsTolerance±1%Power (Watts)150WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 1 kOhms Tolerance ±1% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer Part Number	HS150 1KF
Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 1 kOhms Tolerance ±1% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate - Charcology Axial, Box Failure Rate Charcology Axial, Box Failure Rate Axial, Box Failure Rate	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance1 kOhmsTolerance±1%Power (Watts)150WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance1 kOhmsTolerance±1%Power (Watts)150WCompositionWirewoundTemperature Coefficient±25ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance 1 kOhms Tolerance ±1% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±1% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	1 kOhms
Composition Wirewound Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±1%
Temperature Coefficient ±25ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	150W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±25ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	3.846" L x 1.075" W (97.70mm x 27.30mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.949" (24.10mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HS150 1KF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS150 1KF Payment Methods





















HS150 1KF Shipping Methods













If you have any question about HS150 1KF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com