



HS150 500R J Information



For Reference Only

Part Number HS150 500R J

Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 500 OHM 5% 150W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS150 500R J Specifications

Manufacturer Part Number HS150 500R J Manufacturer Ohmite Category Resistors Package Axial, Box Series ARCOL, HS Resistance 500 Ohms Tolerance ±5% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 500 Ohms Tolerance ±5% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Manufacturer Part Number	HS150 500R J
Package Axial, Box Series ARCOL, HS Resistance 500 Ohms Tolerance ±5% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Package / Case Axial, Box	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance500 OhmsTolerance±5%Power (Watts)150WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Category	Resistors
SeriesARCOL, HSResistance500 OhmsTolerance±5%Power (Watts)150WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, Box		Chassis Mount Resistors
Resistance500 OhmsTolerance±5%Power (Watts)150WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Package	Axial, Box
Tolerance ±5% Power (Watts) 150W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Package / Case Axial, Box	Resistance	500 Ohms
Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Tolerance	±5%
Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Power (Watts)	150W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Temperature Coefficient	±100ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Operating Temperature	-
Mounting Feature Size / Dimension 3.846" L x 1.075" W (97.70mm x 27.30mm) Height - Seated (Max) 0.949" (24.10mm) Lead Style Solder Lugs Package / Case Axial, Box	Features	-
Size / Dimension3.846" L x 1.075" W (97.70mm x 27.30mm)Height - Seated (Max)0.949" (24.10mm)Lead StyleSolder LugsPackage / CaseAxial, Box	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case 0.949" (24.10mm) Solder Lugs Axial, Box	Mounting Feature	Flanges
Lead Style Solder Lugs Package / Case Axial, Box	Size / Dimension	3.846" L x 1.075" W (97.70mm x 27.30mm)
Package / Case Axial, Box	Height - Seated (Max)	0.949" (24.10mm)
	Lead Style	Solder Lugs
Failure Rate -	Package / Case	Axial, Box
	Failure Rate	-
Report errors?		Report errors?

HS150 500R J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS150 500R J Payment Methods





















HS150 500R J Shipping Methods













If you have any question about HS150 500R J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com