

HS1BL MTG

est a Quote

HS1BL MTG Information

Heisener.com	Part Number	HS1BL MTG	
	Manufacturer	TSC America Inc.	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	23
	Description	DIODE, HIGH EFFICIENT, 1A, 100V,	- 20
	Package	DO-219AB	귿
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	Re

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HS1BL MTG Specifications

Manufacturer TSC America Inc. Category Discrete Semiconductor Products Diodes - Rectifiers - Single Diodes - Rectifiers - Single Package DO-219AB Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 100V Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If 950mV @ 1A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 5µA @ 100V Capacitance @ Vr, F 20pF @ 4V, 1MHz Mounting Type Surface Mount Package / Case Do-219AB Supplier Device Package Sub SMA Operating Temperature - Junction 55°C ~ 150°C		
CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	HS1BL MTG
Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCurrent - Reverse Leakage @ Vr20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode Type100VVoltage - DC Reverse (Vr) (Max)1ACurrent - Average Rectified (Io)950mV @ 1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5 μ A @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	-
Current - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If950mV @ 1ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $950mV @ 1A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $50ns$ Current - Reverse Leakage @ Vr $5\muA @ 100V$ Capacitance @ Vr, F $20pF @ 4V$, 1MHzMounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 150° C	Voltage - DC Reverse (Vr) (Max)	100V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	1A
Reverse Recovery Time (trr)50nsCurrent - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	950mV @ 1A
Current - Reverse Leakage @ Vr5µA @ 100VCapacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F20pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	50ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5μA @ 100V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	20pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

HS1BL MTG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HS1BL MTG Payment Methods



HS1BL MTG Shipping Methods



If you have any question about HS1BL MTG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com