



### **HS200 16R F Information**



For Reference Only

Part Number HS200 16R F

Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 16 OHM 1% 200W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HS200 16R F Specifications**

Manufacturer Part Number         HS200 16R F           Manufacturer         Ohmite           Category         Resistors           Package         Axial, Box           Series         ARCOL, HS           Resistance         16 Ohms           Tolerance         ±1%           Power (Watts)         200W           Composition         Wirewound           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         3.531" L x 1.791" W (89.70mm x 45.50mm)           Height - Seated (Max)         1.646" (41.80mm)           Lead Style         M6 Threaded           Package / Case         Axial, Box           Failure Rate         -		
Category         Resistors           Package         Axial, Box           Series         ARCOL, HS           Resistance         16 Ohms           Tolerance         ±1%           Power (Watts)         200W           Composition         Wirewound           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         3.531" L x 1.791" W (89.70mm x 45.50mm)           Height - Seated (Max)         1.646" (41.80mm)           Lead Style         M6 Threaded           Package / Case         Axial, Box           Failure Rate         -	Manufacturer Part Number	HS200 16R F
Chassis Mount Resistors  Package Axial, Box ARCOL, HS Resistance 16 Ohms  Tolerance ±1% Power (Watts) 200W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance16 OhmsTolerance±1%Power (Watts)200WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance16 OhmsTolerance±1%Power (Watts)200WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance16 OhmsTolerance±1%Power (Watts)200WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1%  Power (Watts) 200W  Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature - Features - Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm)  Height - Seated (Max) 1.646" (41.80mm)  Lead Style M6 Threaded  Package / Case Axial, Box  Failure Rate -	Series	ARCOL, HS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±100ppm/°C  Operating Temperature  - Features  - Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  3.531" L x 1.791" W (89.70mm x 45.50mm)  Height - Seated (Max)  Lead Style  M6 Threaded  Package / Case  Failure Rate  -	Resistance	16 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Tolerance	±1%
Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm)  Height - Seated (Max) 1.646" (41.80mm)  Lead Style M6 Threaded  Package / Case Axial, Box  Failure Rate -	Power (Watts)	200W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm)  Lead Style M6 Threaded  Package / Case Axial, Box  Failure Rate	Temperature Coefficient	±100ppm/°C
Coating, Housing Type  Mounting Feature  Flanges  Size / Dimension  3.531" L x 1.791" W (89.70mm x 45.50mm)  Height - Seated (Max)  1.646" (41.80mm)  Lead Style  M6 Threaded  Package / Case  Axial, Box  Failure Rate  -	Operating Temperature	-
Mounting Feature  Size / Dimension  3.531" L x 1.791" W (89.70mm x 45.50mm)  Height - Seated (Max)  1.646" (41.80mm)  Lead Style  M6 Threaded  Package / Case  Axial, Box  Failure Rate  -	Features	-
Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm)  Height - Seated (Max) 1.646" (41.80mm)  Lead Style M6 Threaded  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  M6 Threaded  Package / Case  Axial, Box  Failure Rate  -	Mounting Feature	Flanges
Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	3.531" L x 1.791" W (89.70mm x 45.50mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	1.646" (41.80mm)
Failure Rate -	Lead Style	M6 Threaded
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

#### **HS200 16R F Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HS200 16R F Payment Methods**



















### **HS200 16R F Shipping Methods**













If you have any question about HS200 16R F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com