

HS200 4R F Information



For Reference Only

Part Number HS200 4R F Manufacturer Ohmite Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 4 OHM 1% 200W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS200 4R F Specifications

Manufacturer Part Number HS200 4R F Manufacturer Ohmite Category Resistors Package Axial, Box Series ARCOL, HS Resistance 4 Ohms Tolerance ±1% Power (Watts) 200W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 4 Ohms Tolerance ±1% Power (Watts) 200W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Manufacturer Part Number	HS200 4R F
Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 4 Ohms Tolerance ±1% Power (Watts) 200W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Manufacturer	Ohmite
Package Axial, Box Series ARCOL, HS Resistance 4 Ohms Tolerance ±1% Power (Watts) 200W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Heigh - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Category	Resistors
SeriesARCOL, HSResistance4 OhmsTolerance±1%Power (Watts)200WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance4 OhmsTolerance±1%Power (Watts)200WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1% Power (Watts) 200W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Resistance	4 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.531" L x 1.791" W (89.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Tolerance	±1%
Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Power (Watts)	200W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±100ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 3.531" L x 1.791" W (89.70mm x 45.50mm) Height - Seated (Max) 1.646" (41.80mm) Lead Style M6 Threaded Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate 1.646" (41.80mm) M6 Threaded Axial, Box	Mounting Feature	Flanges
Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	3.531" L x 1.791" W (89.70mm x 45.50mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	1.646" (41.80mm)
Failure Rate -	Lead Style	M6 Threaded
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HS200 4R F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS200 4R F Payment Methods





















HS200 4R F Shipping Methods













If you have any question about HS200 4R F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com