

HS25 3R9 J Information



For Reference Only

Part Number HS25 3R9 J Manufacturer Ohmite Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 3.9 OHM 5% 25W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS25 3R9 J Specifications

Manufacturer Part Number HS25 3R9 J Manufacturer Ohmite Category Resistors Package Axial, Box Series ARCOL, HS Resistance 3.9 Ohms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate Penger arrors?		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 3.9 Ohms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer Part Number	HS25 3R9 J
Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 3.9 Ohms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer	Ohmite
Package Axial, Box Series ARCOL, HS Resistance 3.9 Ohms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Heigh - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Category	Resistors
SeriesARCOL, HSResistance3.9 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance3.9 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	ARCOL, HS
Power (Watts) Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate -	Resistance	3.9 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Tolerance	±5%
Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	25W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±100ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.583" (14.80mm) Solder Lugs Axial, Box -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.075" L x 0.559" W (27.30mm x 14.20mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.583" (14.80mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
Report crists:		Report errors?

HS25 3R9 J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS25 3R9 J Payment Methods



















HS25 3R9 J Shipping Methods













If you have any question about HS25 3R9 J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com