

## **HS25 4R F Information**



For Reference Only

Part Number HS25 4R F Manufacturer Ohmite Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 4 OHM 1% 25W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HS25 4R F Specifications**

Manufacturer Part NumberHS25 4R FManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance4 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		
CategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance4 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	HS25 4R F
Package         Axial, Box           Series         ARCOL, HS           Resistance         4 Ohms           Tolerance         ±1%           Power (Watts)         25W           Composition         Wirewound           Temperature Coefficient         ±100ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         1.075" L x 0.559" W (27.30mm x 14.20mm)           Height - Seated (Max)         0.583" (14.80mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance4 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance4 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.075" L x 0.559" W (27.30mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance 4 Ohms Tolerance ±1% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±1%  Power (Watts) 25W  Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max) 0.583" (14.80mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Series	ARCOL, HS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±100ppm/°C  Operating Temperature  - Features  - Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Resistance	4 Ohms
Composition Wirewound  Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max) 0.583" (14.80mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Tolerance	±1%
Temperature Coefficient ±100ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max) 0.583" (14.80mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Power (Watts)	25W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm)  Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±100ppm/°C
Coating, Housing Type  Mounting Feature  Flanges  Size / Dimension  1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max)  0.583" (14.80mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Operating Temperature	-
Mounting Feature  Size / Dimension  1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  Flanges  1.075" L x 0.559" W (27.30mm x 14.20mm)  Solder Lugs  Axial, Box	Features	-
Size / Dimension 1.075" L x 0.559" W (27.30mm x 14.20mm)  Height - Seated (Max) 0.583" (14.80mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  0.583" (14.80mm)  Solder Lugs	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.075" L x 0.559" W (27.30mm x 14.20mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.583" (14.80mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

### **HS25 4R F Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HS25 4R F Payment Methods**





















## **HS25 4R F Shipping Methods**













If you have any question about HS25 4R F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com