

HS250 1R5 F

HS250 1R5 F Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HS250 1R5 F Specifications

ManufacturerOhmiteCategoryResistorsChassis Mount ResistorsPackageAxial, BoxPackageARCOL, HSResistance1.5 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTolppm/°COpprating Temperature-Features-Coating, Housing TypeHangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Package / CaseAxia, Box		
CategoryResistorsPackageChassis Mount ResistorsPackageAxial, BoxSeriesARCOL, HSResistance1.5 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTomperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeHangesSize / DimensionA.19" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)ModelLead StyleMot ThreadedFakuresAxial, BoxFaiture RateAxial, Box	Manufacturer Part Number	HS250 1R5 F
Chassis Mount ResistorsPackageAxial, BoxSeriesARCOL, HSResistance1.5 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)AftereadedPackage / CaseAxial, BoxFailure Rate-	Manufacturer	Ohmite
PackageAxia, BoxSeriesARCOL, HSResistance1.5 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Cotating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleAini BoxFalure Rate-Falure Rate-Forage / Case-Falure Rate-Falure Rate-<	Category	Resistors
SeriesARCOL, HSResistance1.5 OhmsTolerance±1%Power (Wats)250WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Cotaing, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)I.646" (41.80mm)Lead StyleAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance1.5 OhmsTolerance±1%Power (Wats)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)M6 ThreadedPackage / CaseAxia, BoxFailure Rate-	Package	Axial, Box
Tolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (1.80mm)Height - Seated (Max)Mo ThreadedLead StyleMo ThreadedPackage / CaseAxial, BoxFailure Rate-	Series	ARCOL, HS
Power (Watts)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMoi ThreadedPackage / CaseAxial, BoxFailure Rate-	Resistance	1.5 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMot ThreadedPackage / CaseAxial, BoxFailure Rate-	Tolerance	$\pm 1\%$
Temperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMo ThreadedPackage / CaseAxial, BoxFailure Rate-	Power (Watts)	250W
Operating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMo ThreadedPackage / CaseAxial, BoxFailure Rate-	Composition	Wirewound
Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Temperature Coefficient	±100ppm/°C
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Operating Temperature	-
Mounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Features	-
Size / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Coating, Housing Type	Aluminum
Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Mounting Feature	Flanges
Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	4.319" x 1.791" (109.70mm x 45.50mm)
Package / CaseAxial, BoxFailure Rate-	Height - Seated (Max)	1.646" (41.80mm)
Failure Rate -	Lead Style	M6 Threaded
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

E-mail: salesdept@heisener.com

HS250 1R5 F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

HS250 1R5 F Payment Methods



If you have any question about HS250 1R5 F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com