

HS250 80R F

HS250 80R F Information





E-mail: salesdept@heisener.com

Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HS250 80R F Specifications

ManufacturerOhmiteCategoryResistorsChassis Mount ResistorsPackageAxial, BoxPackageARCOL, HSResistance80 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeHangsaSize / Dimension4.319"x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Package / CaseAxial, Box		
CategoryResistorsPackageAxial, BoxPackageAxial, BoxSeriesARCOL, HSResistance80 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTomperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)Mo ThreadedPackage / CaseAxial, BoxFalure Rate-	Manufacturer Part Number	HS250 80R F
Chassis Mount ResistorsPackageAxial, BoxSeriesARCOL, HSResistance80 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)M6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance80 OhmsTolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Cotating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)Mo Stated (Max)Lead StyleAinal BoxPackage / CaseAxial, BoxFalure Rate-Folure Rate </td <td>Category</td> <td>Resistors</td>	Category	Resistors
SeriesARCOL, HSResistance80 OhmsTolerance±1%Power (Wats)250WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Cotaing, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)I.646" (41.80mm)Lead StyleAkai, BoxFailure Rate-		Chassis Mount Resistors
Resistance80 OhmsTolerance±1%Power (Wats)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)M6 ThreadedPackage / CaseAxial, Box	Package	Axial, Box
Tolerance±1%Power (Watts)250WCompositionWirewoundTemperature Coefficient±100pm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)Mo ThreadedLead StyleMo ThreadedPackage / CaseAxial, BoxFailure Rate-	Series	ARCOL, HS
Power (Watts)250WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.646" (41.80mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMo ThreadedPackage / CaseAxial, BoxFailure Rate-	Resistance	80 Ohms
CompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeaturesFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMot ThreadedPackage / CaseAxial, BoxFailure Rate-	Tolerance	$\pm 1\%$
Temperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleMo ThreadedPackage / CaseAxial, BoxFailure Rate-	Power (Watts)	250W
Operating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Composition	Wirewound
Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Temperature Coefficient	±100ppm/°C
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Operating Temperature	-
Mounting FeatureFlangesSize / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Features	-
Size / Dimension4.319" x 1.791" (109.70mm x 45.50mm)Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Coating, Housing Type	Aluminum
Height - Seated (Max)1.646" (41.80mm)Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Mounting Feature	Flanges
Lead StyleM6 ThreadedPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	4.319" x 1.791" (109.70mm x 45.50mm)
Package / CaseAxial, BoxFailure Rate-	Height - Seated (Max)	1.646" (41.80mm)
Failure Rate -	Lead Style	M6 Threaded
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HS250 80R F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EVARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HS250 80R F Payment Methods



HS250 80R F Shipping Methods



If you have any question about HS250 80R F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com