



HS2C3M20C Information



For Reference Only

Part Number HS2C3M20C Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Circular Connectors

Description CONN PLUG MALE 3POS GOLD

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS2C3M20C Specifications

Manufacturer Part Number HS2C3M20C Manufacturer Switchcraft Inc. Category Connectors, Interconnects Package - Series Dura-Pull?, HS Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesDura-Pull?, HSConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-	Manufacturer Part Number	HS2C3M20C
Package-SeriesDura-Pull?, HSConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-	Manufacturer	Switchcraft Inc.
Package-SeriesDura-Pull?, HSConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-	Category	Connectors, Interconnects
SeriesDura-Pull?, HSConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-	Series	Dura-Pull?, HS
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated L25VAC/DC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DCCurrent Rating-	Shell Size - Insert	-
Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Termination	Crimp or Solder
Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Fastening Type	Push-Pull
Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Orientation	Keyed
Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Ingress Protection	IP66/67/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated 125VAC/DC Current Rating -	Shell Material, Finish	Copper Alloy, Nickel Plated, Electroless
Voltage - Rated 125VAC/DC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielded
•	Voltage - Rated	125VAC/DC
Report errors?	Current Rating	-
*		Report errors

HS2C3M20C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS2C3M20C Payment Methods


































If you have any question about HS2C3M20C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com