

HS2P2F20 Information



For Reference Only

Part Number HS2P2F20

Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT FMALE 2POS GOLD

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS2P2F20 Specifications

Manufacturer Part Number HS2P2F20 Manufacturer Switchcraft Inc. Category Connectors, Interconnects Circular Connectors Package - Series Dura-Pull?, HS Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC Current Rating 10A		
CategoryConnectors, InterconnectsPackage-SeriesDura-Pull?, HSConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel MountTerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC	Manufacturer Part Number	HS2P2F20
Package-SeriesDura-Pull?, HSConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel MountTerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC	Manufacturer	Switchcraft Inc.
Package - Dura-Pull?, HS Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Category	Connectors, Interconnects
SeriesDura-Pull?, HSConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel MountTerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel MountTerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC	Package	-
Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel MountTerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC	Series	Dura-Pull?, HS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated - Contact Finish Shielded - Voltage - Rated - Contact Finish Shielded - Voltage - Rated	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Number of Positions	2
Mounting TypePanel MountTerminationCrimp or SolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC	Shell Size - Insert	-
Termination Crimp or Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Mounting Type	Panel Mount
Orientation Keyed Ingress Protection IP66/67/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Termination	Crimp or Solder
Ingress ProtectionIP66/67/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishCopper Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated125VAC/DC	Fastening Type	Push-Pull
Shell Material, Finish Copper Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Orientation	Keyed
Contact Finish Gold Features Shielded Voltage - Rated 125VAC/DC	Ingress Protection	IP66/67/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated 125VAC/DC	Shell Material, Finish	Copper Alloy, Nickel Plated, Electroless
Voltage - Rated 125VAC/DC	Contact Finish	Gold
	Features	Shielded
Current Rating 10A	Voltage - Rated	125VAC/DC
Current Tutting	Current Rating	10A
Report errors?		Report errors?

HS2P2F20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS2P2F20 Payment Methods





















HS2P2F20 Shipping Methods













If you have any question about HS2P2F20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com